



FCC 47 CFR PART 15 SUBPART B

TEST REPORT

FOR

16-port RS-232/422/485 Serial Device Server
8-port RS-232/422/485 Serial Device Server

Model : EKI-1526, EKI-1528

Trade Name: Advantech

Issued to

Advantech Co., Ltd.

No. 1, Alley 20, Lane 26, Rueiguang Road , Neihu District, Taipei 114, Taiwan, R.O.C.

Issued by

Global Certification Corp.

EMI Test Site	Sansia Lab	NO.34-3,Zihhe Rd.,Sansia Township,Taipei County 237, Taiwan ,R.O.C.
EMC Test Site	Sijhih office and Lab	No. 112-3. Sec.2. Siangjhang Rd. Sijhih City. Taipei County 221, Taiwan(R.O.C.)



Note: This test refers exclusively to the test presented test model and sample. This report shall not be reproduced except in full, without the written approval of Global Certification Corporation. This document may be altered or revised by Global Certification Corporation. Personnel only, and shall be noted in the revision section of the document.



TABLE OF CONTENTS	2
1. GENERAL INFORMATION	3
1.1 DESCRIPTION OF THE TESTED SAMPLES	4
1.2 I/O PORT OF THE EUT	4
1.3 TEST METHODOLOGY	5
1.4 DESCRIPTION OF THE SUPPORT EQUIPMENTS	6
1.5 FEATURES OF EUT	7
2. INSTRUMENT AND CALIBRATION	8
2.1 MEASURING INSTRUMENT CALIBRATION	8
2.2 TEST AND MEASUREMENT EQUIPMENT	8
2.3 TEST PERFORMED	9
2.4 APPENDIX	9
3. CONDUCTED EMISSION MEASUREMENT	12
3.1 TEST SET-UP	12
3.2 LIMIT	12
3.3 TEST PROCEDURE	12
3.4 TEST SPECIFICATION	13
3.5 RESULT	13
3.6 TEST DATA	13
4. RADIATED EMISSION MEASUREMENT	14
4.1 TEST SETUP	14
4.2 LIMIT	15
4.3 TEST PROCEDURE	15
4.4 TEST SPECIFICATION	15
4.5 RESULT	15
4.6 TEST DATA	15
5. MODIFICATION LIST FOR EMC COMPLYING TEST	16
APPENDIX 1	
PHOTOS OF TEST CONFIGURATION	
APPENDIX 2	
TEST DATA	
PHOTOS OF EUT	



1. GENERAL INFORMATION

Applicant : Advantech Co., Ltd.
Address : No. 1, Alley 20, Lane 26, Rueiguang Road , Neihu District, Taipei 114, Taiwan, R.O.C.
Manufacturer : Advantech Co., Ltd.
Address : No. 1, Alley 20, Lane 26, Rueiguang Road , Neihu District, Taipei 114, Taiwan, R.O.C.
EUT : 16-port RS-232/422/485 Serial Device Server 8-port RS-232/422/485 Serial Device Server
Model Name : EKI-1526, EKI-1528
Model Differences : The difference between series of models EKI-1526 and EKI-1528 are shown as below:

	EKI-1526	EKI-1528
Description	16-port RS-232/422/485 Serial Device Server	8-port RS-232/422/485 Serial Device Server
Power Input	90 to 260 VAC	90 to 260 VAC
Number of LAN ports	2	2
Number of Serial ports	16	8
Serial Type	RS-232/422/485	RS-232/422/485
Baud Rate	50 bps to 921.6 Kbps	50 bps to 921.6 Kbps
PCB	EKI-1526	As same as EKI-1526

The PCB layout and circuit and EMI characteristic is similar. The model EKI-1526 is worst case, and the final test data were shown in this test report.

Is here with confirmed to comply with the requirements set out in the FCC Rules and Regulations Part 15 Subpart B and CISPR PUB. 22 and the measurement procedures were according to ANSI C63.4-2003. The said equipment in the configuration described in this report shows the maximum emission levels emanating from equipment are within the compliance requirements.

FCC part 15 subpart B

IC ICES-003

Class A

Receipt Date : 07/29/2008

Final Test Date : 08/07/2008

Taipei, Taiwan

AUG.07 , 2008

Albert Tsai / Manager

(Place)

(Date)

(Signature)

Designation Number: TW1030



1.1 DESCRIPTION OF THE TESTED SAMPLES

EUT

EUT Type : ☐Proto Type ☒Engineer Type ☐Mass Production

Condition when received : ☒Good ☐Damage :

EUT Name : 16-port RS-232/422/485 Serial Device Server
8-port RS-232/422/485 Serial Device Server

Applicant : Advantech Co., Ltd.

Manufacturer : Advantech Co., Ltd.

Model Number : EKI-1526, EKI-1528

Serial Number : N/A

FCC ID : N/A

Used Power : ☒AC POWER ☐DC POWER

Power From : ☐N/A ☒Inside ☐Outside
☐Adaptor ☐BATTERY ☐Power Supply ☐DC Power Source
☒Support Unit Power Board

Power Supply Type : ☒Switching ☐Linear

Power Cord (Input) : AC 110 V 60 Hz 3 Pin 1.8 m Un-Shielded

The frequency of the EUT :

OSC/Clock Frequencies : 14.74MHz, 33.33MHz

1.2 I/O PORT OF THE EUT

I/O port type	Q'ty	Tested with	Connect type	Note
1) CONSOLE Port	1	0	Metal	Floating
2) RJ-45 Port	16	0	Metal	Floating
3) LAN Port	2	2	Metal	



1.3 TEST METHODOLOGY

EUT SYSTEM OPERATION

1. The EUT was configured according to ANSI C63.4 – 2003 Section 5.2, 7.1, 7.2 & CISPR 22 - 2005.
 2. All I/O ports were connected to the appropriate peripherals.
 3. Photos of test configuration please refer to appendix 1 or 1.4 Setup Diagram.
 4. Turn on all the power of EUT and peripheral.
 5. The remote PC1 links the remote PC2 and channels packet switching via EUT.
 6. Perform the EMI testing procedures, and measure the maximum emission noise.
- All peripherals and cables are listed below (including internal device)

DECISION OF FINAL TEST MODE

1. The following test mode were scanned during the preliminary test:

Mode 1: 100Mbps

Mode 2: 10Mbps

2. After the preliminary scan, the following test mode was found to produce the highest emission level.

Conduction: Mode 1

Radiation: Mode 1


Then, the EUT configuration and cable configuration of the above highest emission mode was chosen for all final test item



1.4 DESCRIPTION OF THE SUPPORT EQUIPMENTS

Setup Diagram

See test photographs attached in appendix I for the actual connections between EUT and support equipment.



Support Equipment

Peripherals Devices:

OUTSIDE SUPPORT EQUIPMENT							
No.	Equipment	Model	Serial No.	FCC ID/ BSMI ID	Trade name	Data Cable	Power Cord
01	PC	M35	0545TDT0 0856	R33142	Acer	Unshielded 10m	Unshielded 1.8m
02	PC	A13	L3AB112	R33B65	IBM	Unshielded 10m	Unshielded 1.8m
03	MONITOR	TFT22W90 PSA	E9377JA0 00166	R33037	AOC	Shielded 1.8M	Unshielded 1.8m
04	MONITOR	V22ECBF	3M6U077 02009	R31282	TATUNG	Shielded 1.6M	Unshielded 1.8m
05	MOUSE	M-S34	HCA4170 0559	DEL2110 29/4862A 011	Logitech	Shielded 1.8M~PS2	N/A
06	MOUSE	M-S34	HCA4170 0532	DEL2110 29/4862A 011	Logitech	Shielded 1.8M~PS2	N/A
07	KEY BOARD	Y-SM46	N/A	T51160	Logitech	Shielded	N/A



						1.4M/ps2	
08	KEY BOARD	RT7D00	TH-0332TR-37171-16R-3087	AQ6-7D0080COB/3892C595	DELL	Shielded 1.9M/PS2	N/A
INSIDE SUPPORT EQUIPMENT							
No.	Equipment	Model	Serial No.	FCC ID/BSMI ID	Trade name	Data Cable	Power Cord
01	Main Board	EKI-1526/1328 A1 01-2	19C3152601	DOC	N/A	Unshielded 10m	Unshielded 0.2m
02	Power Board	N/A	AC77-02	DOC	N/A	N/A	Unshielded 0.2m

Note: All the above equipment /cable were placed in worse case position to maximize emission signals during emission test

Grounding: Grounding was in accordance with the manufacturer's requirement and conditions for the intended use.

1.5 FEATURES OF EUT: PLEASE REFER TO USER MANUAL OR PRODUCT SPECIFICATION.



2. INSTRUMENT AND CALIBRATION

2.1 MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in the report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

2.2 TEST AND MEASUREMENT EQUIPMENT

The following list contains measurement equipment used for testing. The equipment conforms to the requirement of CISPR 16-1, ANSI C63.2 and. Other required standards.

Calibration of all test and measurement, including any accessories that may effect such calibration, is checked frequently to ensure the accuracy. Adjustments are made and correction factors are applied in accordance with the instructions contained in the respective.

TABLE 1 LIST OF TEST AND MEASUREMENT EQUIPMENT

Conducted Emission Measurement					
Instrument	Manufacturer	Model No.	Serial No.	Calibration Due Date	Note
Test Receiver	ROHDE & SCHWARZ	ESCI	100438	Apr.29.2009	
LISN	SCHAFFNER	NNB41	03/10015	Jun.10.2009	For EUT
LISN	EMCO	3825/2	9001-1589	Apr.09.2009	For Support Unit
RF CABLE	MIYAZAKI	5D-F8	002	May.24.2009	
50ohm Terminal	N/A	N/A	TM003	Apr,18,2009	
Radiated Emission Measurement					
Instrument	Manufacturer	Model No.	Serial No.	Calibration Due Date	Note
Test Receiver	AFJ	ER55R	55300508277	May.20.2009	
Bilog Antenna	SUNOL	JB1	A052104	SEP.30.2008	
Turn table	EMCO	2080	9508-1805	N/A	



Controller	EMCO	2090	9804-1328	N/A	
Amplifier	G.W	GAP-801	EF150001	Jul.18.2009	
EMC Analyzer	AGILENT	E7401A	MY42000145	May.23.2009	
RF Cable	BELDEN	RG-8/U	E037	Jun.07.2009	
Thermo-Hygro meter	WISEWIND	4-IN-1	0412	Apr.10.2009	

✂ Calibration interval of instruments listed above is one year

2.3 TEST PERFORMED

Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver which bandwidth is set at 9 KHz.

Radiated emissions were investigated over the frequency range from 30MHz to 1000MHz using a receiver which bandwidth is set at 120KHz. Radiated measurement was performed at distance that from an antenna to EUT is 10meters.

2.4 APPENDIX

Appendix A: Measurement Procedure for Main Power Port Conducted Emissions

The measurements are performed in a Global lab's room; The EUT was placed on non-conductive 1.0m x 1.5m table, which is 0.8 meters above an earth-grounded.

Power to the EUT was provided through the LISN which has the Impedance (50ohm/50uH) vs. Frequency Characteristic in accordance with the standard. Powers to the LISNs were filtered to eliminate ambient signal interference and these filters were bonded to the ground plane. Peripheral equipment required to provide a functional system (support equipment) for EUT testing was powered from the second LISN through a ganged, metal power outlet box which is bonded to the ground plane at the LISN.

If the EUT is supplied with a flexible power cord, the power cord length in excess of the distance separating the EUT from the LISN shall be folded back and forth at the center of the lead so as to form a bundle not exceeding 40cm in length. If the EUT is provided with a permanently coiled power cord, bundling of the cord is not required. If the EUT is supplied without a power cord, the EUT shall be connected to the LISN by a power cord of the type specified by the manufacturer which shall not be longer than 1 meter. The excess power cord shall be bundled as described above. If a non-flexible power cord is provided with the EUT, it shall be cut to the length necessary to attach the EUT to the LISN and shall not be bundled.

The interconnecting cables were arranged and moved to get the maximum measurement. Both the line of power cord, hot and neutral, was measured.



The highest emissions were analyzed in details by operating the spectrum analyzer in fixed tuned mode to determine the nature of the emissions and to provide information which could be useful in reducing their amplitude.

Appendix B: Test Procedure for Radiated Emissions

Preliminary Measurements in the Anechoic Chamber

The radiated emissions are initially measured in the anechoic chamber at a measurement distance of 3 meters. Desktop EUT are placed on a wooden stand 0.8 meter in height. The measurement antenna is 3 meters from the EUT. The test setup in anechoic chamber is the same as open site. The turntable rotated 360°. The antenna height is 1m. The primary objective of the radiated measurements in the anechoic chamber is to identify the frequency spectrum in the absence of the electromagnetic environment existing on the open test site. The frequencies can then be pre-selected on the open test site to obtain the corresponding amplitude. The initial scan is made with the spectrum analyzer in automatic sweep mode. The spectrum peaks are then measured manually to determine the exact frequencies.

Measurements on the Open Site or Chamber

The radiated emissions test will then be repeated on the open site or chamber to measure the amplitudes accurately and without the multiple reflections existing in the shielded room. The EUT and support equipments are set up on the turntable. Desktop EUT are set up on a wooden stand 0.8 meter above the ground.

For the initial measurements, the receiving antenna is varied from 1-4 meter height and is changed in the vertical plane from vertical to horizontal polarization at each frequency. Both reading are recorded with the quasi-peak detector with 120KHz bandwidth. For frequency between 30 MHz and 1000MHz, the reading is recorded with peak detector or quasi-peak detector.

At the highest amplitudes observed, the EUT is rotated in the horizontal plane while changing the antenna polarization in the vertical plane to maximize the reading. The interconnecting cables were arranged and moved to get the maximum measurement. Once the maximum reading is obtained, the antenna elevation and polarization will be varied between specified limits to maximize the readings.



Appendix C: Warning Labels

Label Requirements

A Class B digital device subject to certification by the FCC shall carry a warning label which includes the following statement:

*** * * W A R N I N G * * ***

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Appendix D: Warning Statement

Statement Requirements

The operator's manual for a Class A digital device shall contain the following statements or their equivalent:

*** * * W A R N I N G * * ***

This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his own expense.

Notice: The changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.


* * * * *

If the EUT was tested with special shielded cables the operator's manual for such product shall also contain the following statements or their equivalent:

Shielded interface cables and/or AC power cord, if any, must be used in order to comply with the emission limits.

3. CONDUCTED EMISSION MEASUREMENT

3.1 TEST SET-UP (PLEASE REFER TO APPENDIX 1)



3.2 LIMIT

Frequency range (MHz)	CLASS A		CLASS B	
	QP dB(uV)	Average dB(uV)	QP dB(uV)	Average dB(uV)
0.15-0.5	79 dBuV	66 dBuV	66 - 56 dBuV	56 - 46 dBuV
0.5-5.0	73 dBuV	60 dBuV	56 dBuV	46 dBuV
5.0-30.0	73 dBuV	60 dBuV	60 dBuV	50 dBuV

Remark: In the above table, the tighter limit applies at the band edges.

3.3 TEST PROCEDURE

The EUT and simulators are connected to the main power through a line impedance stabilization network (LISN). It provides a 50 ohm / 50 μ H coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50 ohm / 50 μ H coupling impedance with 50 ohm termination. (Please refer to the block diagram of the test setup and photograph.)

Both sides of AC line are checked for the maximum conducted emission interference. In order to find the maximum emissions, the relating positions of equipment and all of the interference cables must be changed according to CISPR22 regulation: The measurement procedure on conducted emission interference.

The resolution bandwidth of the field strength meter is set at 9KHz



3.4 TEST SPECIFICATION

ANSI C63.4 – 2003 Section 5.2, 7.1, 7.2 & CISPR 22 – 2005 CLASS A

3.5 RESULT: PASSED

EMI Receiver/Spectrum Analyzer Configuration (for the frequencies tested)

Frequency Range:	150KHz--30MHz
Detector Function:	Quasi-Peak / Average Mode
Resolution Bandwidth:	9KHz


3.6 TEST DATA:

Please refer to appendix 2



4. RADIATED EMISSION MEASUREMENT

4.1 TEST SETUP (PLEASE REFER TO APPENDIX 1)





4.2 LIMIT

Frequency	Class A		Class B	
MHz	Distance (Meter)	Limit dB μ V/m	Distance (Meter)	Limit dB μ V/m
30 ~ 230	10	40	10	30
230 ~ 1000	10	47	10	37
Above 1000	10	49.5	10	43.5

Remark: In the above table, the tighter limit applies at the band edges

4.3 TEST PROCEDURE

The EUT and its simulators are placed on turn table, non-conductive and wooden table, which is 0.8 meter above ground. The turn table rotates 360 degree to determine the position of the maximum emission level. The EUT was positioned such that distance from antenna to the EUT is 10 meters.

The antenna is moved up and down between 1 meter to 4 meter to receive the maximum emission level.

Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission, all of the interference cables must be manipulated according to CISPR regulation: the test procedure of the radiated emission measurement.

The bandwidth set on the field strength is 120 KHz when the frequency range is below 1GHz

4.4 TEST SPECIFICATION

ANSI C63.4 – 2003 Section 5.2, 7.1, 7.2 & CISPR 22 – 2005 CLASS A

4.5 RESULT: PASSED

The radiated mission test was passed at minimum margin :
Vertical 61.37 MHz/ 36.93 dBuV/m, Antenna Height 1.8 Meter,
Turn Table 220 degree,

4.6 TEST DATA:

Please refer to appendix 2



5. MODIFICATION LIST FOR EMC COMPLYING TEST

The modification is solely made by the applicant.

Appendix

Appendix A: Summary of Test Result

Appendix B: The test photograph of EUT

Appendix C: The Detail Photograph of EUT

Appendix A: Summary of Test Result

**** EMC Test Result: The EUT has been pass the all measurements. ****

The uncertainty is calculated in accordance with CISPR16-4-2, the total uncertainty for this test is as follows:

Uncertainty of Conducted Emission Measurement

Contribution	Probability Distribution	150KHz – 30MHz
Receiver reading	Normal (k=2)	± 0.2
Cable loss	Normal (k=2)	± 0.2
AMN insertion loss	Rectangular	± 0.2
RCV/SPA specification	Rectangular	± 0.9
combined standard uncertainty $U_e(y)$	normal	± 1.0
Measuring uncertainty for a level of confidence of 95% $U=2U_e(y)$	normal (k=2)	± 2.0

Uncertainty of Radiated Emission Measurement

Contribution	Probability Distribution	30MHz~1GHz
Receiver reading	Normal (k=2)	± 0.5
Cable loss calibration	Normal (k=2)	± 0.3
Antenna factor calibration	Rectangular	± 1.5
Pre Amplifier Gain calibration	Rectangular	± 0.5
RCV/SPA specification	Rectangular	± 0.9
combined standard uncertainty $U_e(y)$	normal	± 1.1
Measuring uncertainty for a level of confidence of 95% $U=2U_e(y)$	normal (k=2)	± 2.2



SAMPLE OF FCC DOC LABEL 1

This device complies with part 15 of the FCC Rules.
Operation is subject to the following two conditions: (1)
This device may not cause harmful interference. And (2)
this device must accept any interference received, including
interference that may cause undesired operation.

SAMPLE OF FCC DOC LABEL 2



Trade Name
Model Number



Global Certification Corp.

Appendix 1

PHOTOS OF TEST CONFIGURATION



Global Certification Corp.
CONDUCTED POWER LINE TEST

Report No. : F872903



Front View



Rear View



RADIATED EMISSION TEST



Front View



Rear View



Global Certification Corp.

Appendix 2

TEST DATA




Test Data Of Conducted Emission Measurement (LINE)



環球認證有限公司
Global Certification Corp.

Global Certification Corp.
No.112-3, Sec.2, Siangjhang Rd.
Sijhih City, Taipei County 221, Taiwan
TEL:886-2-26426992 FAX:886-2-26487450
WebSite: <http://www.gcc.tw>

Data: 1



Site : Conduction Test Site 1
Condition : CISPR22 CLASS-A QP LINE RBW:9KHz VBW:300KHz SWT:0.10sec
EUT : EKI-1526
MODE : AC 110V / 60Hz
MEMO :

	Freq	Level	Over	Limit	LISN	Cable	
	MHz	dBuV	Limit	Line	Factor	Loss	Remark
			dB	dBuV	dB	dB	
1	0.21	42.86	-36.14	79.00	10.10	0.03	Peak
2	0.42	38.48	-40.52	79.00	10.10	0.05	Peak
3	0.98	45.61	-27.39	73.00	10.10	0.09	Peak
4	1.46	40.90	-32.10	73.00	10.10	0.11	Peak
5	8.28	34.39	-38.61	73.00	10.10	0.24	Peak
6	21.83	37.50	-35.50	73.00	10.02	0.37	Peak




Test Data Of Conducted Emission Measurement (NATURAL)



環球認證有限公司
Global Certification Corp.

Global Certification Corp.
No.112-3, Sec.2, Siangjhang Rd.
Sijhih City, Taipei County 221, Taiwan
TEL:886-2-26426992 FAX:886-2-26487450
WebSite: <http://www.gcc.tw>

Data: 2



Site : Conduction Test Site 1
Condition : CISPR22 CLASS-A QP NEUTRAL RBW:9KHz VBW:300KHz SWT:0.10sec
EUT : EKI-1526
MODE : AC 110V / 60Hz
MEMO :

	Freq	Level	Over	Limit	LISN	Cable	
	MHz	dBuV	Limit	Line	Factor	Loss	Remark
			dB	dBuV	dB	dB	
1	0.21	44.22	-34.78	79.00	10.10	0.03	Peak
2	0.42	42.04	-36.96	79.00	10.10	0.05	Peak
3	0.97	44.01	-28.99	73.00	10.10	0.09	Peak
4	1.51	40.47	-32.53	73.00	10.10	0.11	Peak
5	10.13	32.12	-40.88	73.00	10.30	0.25	Peak
6	22.66	37.10	-35.90	73.00	10.36	0.38	Peak



Test Data Of Radiated Emission Measurement (Horizontal)



環球認證有限公司
Global Certification Corp.

Address: No.112-3, Shiang Chang Rd., Sec.2,
Hsi Chin, Taipei Hsien 221, Taiwan, R.O.C.
Tel: 02-26426992 Fax: 02-26487450

Radiated Emission Measurement


File : 872903

Data : #3

Date: 2008/08/05

Time: 下午 02:43:45

Unit : dBuV/m



Site : Open site #1

Limit: EN55022, CISPR22, CNS13438 Class A

Company:

EUT:

Model : EKI-1526

Note: 100Mbps

Polarization: **Horizontal**

Power: AC 110V / 60Hz

Distance: 10m RBW: 100 KHz

Temperature: 30 °C

Humidity: 60 %

Sweep Time: 300 ms

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	
							Detector		degree	Comment
1		113.3750	23.62	6.08	29.70	40.00	-10.30	peak	0	
2	*	250.7000	35.85	4.76	40.61	47.00	-6.39	peak	0	
3		500.1250	20.73	12.10	32.83	47.00	-14.17	peak	0	
4		599.6000	20.97	13.39	34.36	47.00	-12.64	peak	0	
5		699.1250	18.68	15.29	33.97	47.00	-13.03	peak	0	
6		725.4250	16.30	15.55	31.85	47.00	-15.15	peak	0	

*: Maximum data x: Over limit l: over margin

●Reference Only

Receiver:

Spectrum Analyzer: E7401A

Antenna: A052104-071001(10M)

Engineer Signature: JEFF

Amplifier: AMP-EF150001 070719

File : 872903\Data : #3

Page: 1



Test Data Of Radiated Emission Measurement (Vertical)



環球認證有限公司
Global Certification Corp.

Address: No.112-3, Shiang Chang Rd., Sec.2,
Hsi Chin, Taipei Hsien 221, Taiwan, R.O.C.
Tel: 02-26426992 Fax: 02-26487450


Radiated Emission Measurement

File : 872903
EUT : dBuV/m

Data : #4

Date: 2008/08/05

Time: 下午 02:58:56



Site : Open site #1

Limit: EN55022, CISPR22, CNS13438 Class A

Company:

EUT:

Model : EKI-1526

Note: 100Mbps

Polarization: **Vertical**

Power: AC 110V / 60Hz

Distance: 10m RBW: 100 KHz

Temperature: 30 °C

Humidity: 60 %

Sweep Time: 300 ms

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	
							Detector		degree	Comment
1	*	61.3750	37.43	-0.50	36.93	40.00	-3.07	QP	180	220
2	!	113.7250	30.68	6.11	36.79	40.00	-3.21	peak	0	
3		250.5250	34.60	4.75	39.35	47.00	-7.65	peak	0	
4		374.1250	29.68	8.78	38.46	47.00	-8.54	peak	0	
5	!	626.3250	29.76	14.08	43.84	47.00	-3.16	peak	0	
6		750.1000	20.92	15.80	36.72	47.00	-10.28	peak	0	

*: Maximum data x: Over limit !: over margin

●Reference Only

Receiver:

Spectrum Analyzer: E7401A

Antenna: A052104-071001(10M)

Engineer Signature: JEFF

Amplifier: AMP-EF150001 070719

File : 872903\Data : #4

Page: 1



Global Certification Corp.

PHOTO OF EUT

PHOTOS OF EUT



PHOTO OF EUT



Front View of EUT



Rear View of EUT



PHOTO OF EUT



Front View of I/O



Rear View of I/O




PHOTO OF EUT




Inside View of EUT



PHOTO OF EUT




Component Side of Main Board




Solder Side of Main Board



PHOTO OF EUT



Front View of Power Board



Rear View of Power Board