



EMC

TEST REPORT

REPORT NO. : CE88033105

MODEL NO. : IPC-623XX-XXXX

DATE OF TEST : Apr. 3 ~ Apr. 15, 1999

PREPARED FOR : ADVANTECH CO., LTD.

ADDRESS : FL. 4, NO. 108-3, MING-CHUAN ROAD,
SHING-TIEN CITY TAIPEI HSIEN, TAIWAN

PREPARED BY: ADVANCE DATA TECHNOLOGY CORPORATION



Accredited Laboratory

11F, NO.1, SEC.4, NAN-KING EAST RD.,
TAIPEI, TAIWAN, R.O.C.

This test report consists of 68 pages in total. It may be duplicated completely for legal use with the allowance of the applicant. It shall not be reproduced except in full, without the written approval of our laboratory. It should not be used by the client to claim product endorsement by NVLAP or any agency of the U.S. government. The test result in the report only applies to the tested sample.



TABLE OF CONTENTS

1. CERTIFICATION.....	3
2. GENERAL INFORMATION	4
2.1 GENERAL DESCRIPTION OF EUT.....	4
2.2 GENERAL DESCRIPTION OF APPLIED STANDARD.....	5
2.3 DESCRIPTION OF SUPPORT UNITS.....	6
2.4 TEST SETUP.....	7
3. TEST INSTRUMENTS	8
3.1 TEST INSTRUMENTS (EMISSION).....	8
3.2 TEST INSTRUMENTS (IMMUNITY).....	9
3.3 LIMITS OF CONDUCTED AND RADIATED EMISSION.....	10
4. TEST RESULTS (EMISSION).....	11
4.1 RADIO DISTURBANCE	11
4.1.1 EUT OPERATION CONDITION.....	11
4.1.2 TEST DATA OF CONDUCTED EMISSION (A).....	12
4.1.3 TEST DATA OF CONDUCTED EMISSION (B).....	14
4.1.4 TEST DATA OF CONDUCTED EMISSION (C).....	16
4.1.5 TEST DATA OF CONDUCTED EMISSION (D)	18
4.1.6 TEST DATA OF RADIATED EMISSION (A).....	20
4.1.7 TEST DATA OF RADIATED EMISSION (B).....	22
4.1.8 TEST DATA OF RADIATED EMISSION (C).....	24
4.1.9 TEST DATA OF RADIATED EMISSION (D).....	26
4.2 DISTURBANCE IN SUPPLY SYSTEM.....	28
4.2.1 EUT OPERATION CONDITION.....	28
4.2.2 MEASUREMENT DATA OF HARMONICS TEST (A)	29
4.2.3 MEASUREMENT DATA OF HARMONICS TEST (B)	30
4.2.4 MEASUREMENT DATA OF HARMONICS TEST (C)	31
4.3 VOLTAGE FLUCTUATIONS AND FLICKER.....	32
4.3.1 EUT OPERATION CONDITION.....	32
4.3.2 TEST DATA OF VOLTAGE FLUCTUATIONS AND FLICKER (A)	33
4.3.3 TEST DATA OF VOLTAGE FLUCTUATIONS AND FLICKER (B)....	34
4.3.4 TEST DATA OF VOLTAGE FLUCTUATIONS AND FLICKER (C)....	35
4.3.5 TEST DATA OF VOLTAGE FLUCTUATIONS AND FLICKER (D)	36
5. TEST RESULTS (IMMUNITY).....	37
5.1 GENERAL DESCRIPTION	37
5.2 PERFORMANCE CRITERIA DESCRIPTION	37
5.3 EUT OPERATION CONDITION	37
5.4 TEST RESULT OF ELECTROSTATIC DISCHARGE (ESD).....	38
5.5 TEST RESULT OF RADIATED ELECTROMAGNETIC FIELDS (RS).....	39
5.6 TEST RESULT OF ELECTRICAL FAST TRANSIENT (EFT).....	40
5.7 TEST RESULT OF CONDUCTED RADIO FREQUENCY DISTURBANCES (CS) ...	41
5.8 TEST RESULT OF POWER FREQUENCY MAGNETIC FIELD.....	42
5.9 TEST RESULT OF RADIO-FREQUENCY ELECTROMAGNETIC	43
6. PHOTOGRAPHS OF THE TEST CONFIGURATION	44
7. APPENDIX - INFORMATION OF THE TESTING LABORATORY	68



1.

CERTIFICATION

Issue date: Apr. 22, 1999

Product : INDUSTRIAL COMPUTER
Trade Name : ADVANTECH
Model No. : IPC-623XX-XXXX
Applicant : ADVANTECH CO., LTD.
Standard : EN 55022: 1994+A1: 1995+A2: 1997, **EN 50082-2: 1995**
Class A EN 61000-4-2: 1995
EN 61000-3-2: 1995, Class A EN 61000-4-3: 1996
EN 60555-2: 1987 EN 61000-4-4: 1995
EN 61000-3-3: 1995 EN 61000-4-6: 1996
EN 61000-4-8: 1994
ENV 50204: 1995

We hereby certify that one sample of the designation has been tested in our facility from Apr. 3 to Apr. 15, 1999. The test record, data evaluation and Equipment Under Test (EUT) configurations represent herein are true and accurate representation of the measurements of the sample's EMC characteristics under the conditions herein specified.

TESTED BY : _____ , DATE: _____
(Emission) (Chris Yang)

TESTED BY : _____ , DATE: _____
(Immunity) (Dennis Chuang)

CHECKED BY : _____ , DATE: _____
(Ariel Hsieh)

APPROVED BY : _____ , DATE: _____
(Mike Su)

ADVANCE DATA TECHNOLOGY CORPORATION



Accredited Laboratory



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Product : INDUSTRIAL COMPUTER
Model No. : IPC-623XX-XXXX
Power Supply Type : Switching
Power Cord : Nonshielded (1.8 m)

Note: The EUT is an INDUSTRIAL COMPUTER with two USB ports.

The X in model: IPC-623XX-XXXX could be defined as A~Z, 0~9 or blank.
The former XX stands for different backplanes and the latter XXXX stands for different switching power supplies used.

The EUT was tested under the following test modes and configuration:

	MODE 1	MODE 2	MODE 3	MODE 4
MODEL NO.	IPC-623MB-300	IPC-623MB-300X	IPC-623P4-400	IPC-623P4-300R
CPU	Intel Pentium II 450 MHz	Intel Pentium II 350 MHz	Intel Pentium II 450 MHz	Intel Pentium II 333 MHz
BACKPLANE	ADVANTECH, Model: PCA-6114P4	-	ADVANTECH Model: PCA-6120P4	ADVANTECH Model: PCA-6120P4
MOTHER BOARD	-	ASUS Model: P2B	-	-
CPU BOARD	ADVANTECH Model: PCA-6176	-	ADVANTECH Model: PCA-6176	ADVANTECH Model: PCA-6175
VGA CARD	ON BOARD (1600x1200)	CARDEX Model: CD-GX2A44T (1600x1200)	ON BOARD (1600x1200)	SYNNEX Model: B3D-S32 (1280x1024)
SPS	SKYNET, Model: ADT-930C, 300W	DELTA, Model: DPS-338AB- B, 300W	SUNPOWER, Model: SPQ-4400, 400W	ETASIS, Model: EPR-2309 (double power) 300W + 300W
FDD	NEC, Model: FD1231H			
HDD	NEC, Model: DSE1340A, 1.2G			
CD-ROM	ACER, Model : ACER 24X			

The test data of the above four test modes were recorded individually in this report.

The video resolutions of 1600x1200 (for mode 1, 2 & 3) and 1280x1024 (for mode 4) were used during the test.

For more detailed features description, please refer to manufacturer's specification or User's Manual.



2.2 GENERAL DESCRIPTION OF APPLIED STANDARD

According to the manufacturer's request, the EUT was tested with the requirements of the following standards:

EN 55022: 1994+A1: 1995+A2: 1997, Class A	EN 50082-2: 1995
EN 61000-3-2: 1995, Class A	EN 61000-4-2: 1995
EN 60555-2: 1987	EN 61000-4-3: 1996
EN 61000-3-3: 1995	EN 61000-4-4: 1995
	EN 61000-4-6: 1996
	EN 61000-4-8: 1994
	ENV 50204: 1995

All tests are performed and recorded as per above standards.

2.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories are used to form representative test configuration during the tests.

FOR EMISSION TEST

No	Product	Brand	Model No.	Serial No.	I/O Cable
1.	COLOR MONITOR	HP	D2846	JP74912250	Shielded Signal (1.5m) Nonshielded Power (1.8m)
2.	MODEM	ACEEX	1414	980020507	Shielded Signal (1.2m) Nonshielded Power (1.2m)
3.	PRINTER	HP	2225C+	3208S5355	Shielded Signal (1.2m) Nonshielded Power (1.2m)
4.	USB KEYBOARD	BTC	7932	174250046	Shielded Signal (1.7m)
5.	USB MOUSE	DEXIN	A2U800A	71001820	Shielded Signal (1.5m)
6.	PS2 KEYBOARD	FORWARD	FDA-104GA	FDKB8110116	Shielded Signal (1.4m)
7.	RS232 MOUSE	LOGITECH	M-M30	LTR53500777	Shielded Signal (1.9m)
8.	KEYBOARD (for mode 1 only)	FORWARD	FDA-104GA	FDKB8110162	Shielded Signal (1.4m)
9.	MODEM (for mode 2 only)	OPTIQUEST	4500DC	3651700124	Shielded Signal (1.2m) Nonshielded Power (1.2m)
10.	PS2 MOUSE (for mode 2 only)	DEXIN	A2P800A	80102047	Shielded Signal (1.5m)

Note: 1. Support units 4 & 5 were connected to the USB ports of EUT.

2. MODE 4 was tested without USB mouse and USB keyboard (support units 4 & 5).



FOR IMMUNITY TEST

No	Product	Brand	Model No.	Serial No.	I/O Cable
1.	COLOR MONITOR	HP	D2846	JP74912250	Shielded Signal (1.5m) Nonshielded Power (1.8m)
2.	MODEM	GVC	F-1128V1R6	96-191-113003	Shielded Signal (1.25m) Nonshielded Power (1.5m)
3.	PRINTER	HP	C2145A	SG59N16035	Shielded Signal (2.0m) Nonshielded Power (1.8m)
4.	USB KEYBOARD	BTC	7932	D7A140018	Shielded Signal (1.8m)
5.	USB MOUSE	DEXIN	A2U800A	71001824	Shielded Signal (1.5m)
6.	PS2 KEYBOARD	HP	C3758A	K101088	Shielded Signal (1.8m)
7.	RS232 MOUSE	DEXIN	A2R800A	80110026	Shielded Signal (1.5m)
8.	KEYBOARD (for mode 1 only)	FORWARD	FDA-104GA	FDKB8110162	Shielded Signal (1.4m)
9.	MODEM (for mode 2 only)	GVC	F-1114V/R6	853E100	Shielded Signal (1.25m) Nonshielded Power (1.5m)
10.	PS2 MOUSE (for mode 2 only)	DEXIN	A2P800A	80102123	Shielded Signal (1.5m)

Note: 1. Support units 4 & 5 were connected to the USB ports of EUT.

2. MODE 4 was tested without USB mouse and USB keyboard (support units 4 & 5).

2.4 TEST SETUP

Please refer to the photos of test configuration in Item 6.



3. TEST INSTRUMENTS

3.1 TEST INSTRUMENTS (EMISSION)

CONDUCTED EMISSION MEASUREMENT

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
ROHDE & SCHWARZ Test Receiver	ESHS30	828109/007	July 22, 1999
ROHDE & SCHWARZ Artificial Mains Network	ESH2-Z5	892107/003	July 20, 1999
EMCO L.I.S.N.	3825/2	9504-2359	July 20, 1999
Shielded Room	Site 3	ADT-C03	NA

Note: 1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per NAMAS document NIS81.

2. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.

RADIATED EMISSION MEASUREMENT

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
HP Spectrum Analyzer	8594E	3520A01861	Feb. 08, 2000
HP Preamplifier	8447D	2944A08118	June 28, 1999
HP Preamplifier	8347A	3307A01088	Sept. 9, 1999
ROHDE & SCHWARZ TEST RECEIVER	ESVS 10	840241/010	Sept. 10, 1999
SCHWARZBECK Tunable Dipole Antenna	VHA 9103 UHA 9105	E101051 E101055	Nov. 25, 1999
CHASE BILOG Antenna	CBL6111A	1079	July 17, 1999
EMCO Double Ridged Guide Antenna	3115	9312-4192	April 5, 2000
CHANCE Turn Table	U200	9701	NA
CHANCE Tower	AT-100	CM-A003	NA
Open Field Test Site	Site 3	ADT-R03	July 16, 1999

Note: 1. The measurement uncertainty is less than +/- 3dB, which is calculated as per NAMAS document NIS81.

2. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.

CURRENT HARMONICS, VOLTAGE FLUCTUATION AND FLICKER MEASUREMENT

Description & Manufacturer	Model no.	Serial No.	Calibrated Until
KeyTek, Power Arb Waveform Generator	EP72HF	9508346	May 28, 1999
KIKUSUI AC SWITCHING POWER SUPPLY	PCR 4000L	9508355	May 28, 1999

Note: The calibration interval of the above test instruments is 12 months.

And the calibrations are traceable to NML/ROC and NIST/USA.



3.2 TEST INSTRUMENTS (IMMUNITY)

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
KeyTek, ESD Test System	2000	9105240/41	Aug. 9, 1999
KeyTek, ESD Simulator	MZ-15/EC	92022232	April 15, 1999
KeyTek, EFT Generator	CE-40	9508257	Sept. 8, 1999
KeyTek, Capacitive Clamp	CE-40-CCL	9508259	Sept. 8, 1999
ROHDE & SCHWARZ Signal Generator	SMY01	840490/009	Sept. 30, 1999
KALMUS Power Amplifier	LA1000V	091995-1	NA
KALMUS Power Amplifier	757LC	091995-2	NA
HOLADAY Field Probe	HI-4422	89915	Oct. 27, 1999
EMCO BiconiLog Antenna	3141	1001	NA
FCC Coupling Decoupling Network	FCC-801-M3-25	48	NA
FCC Coupling Decoupling Network	FCC-801-M2-25	20	NA
FISCHER CUSTOM COMMUNICATIONS EM Injection Clamp	FCC-203I	50	NA
FCC Coupling Decoupling Network	FCC-801-M1-25	17	NA
BOONTON RF Voltage Meter	9200B	331801AE	Dec. 17, 1999
COMTEST Compact Full Anechoic Chamber (7x3x3 m)	CFAC	ADT-S01	Aug. 4, 1999
HAEFELY Magnetic Field Tester	MAG 100.1	083794-06	NA
COMBINOVA Magnetic Field Meter	MFM10	224	Aug. 26, 1999

Note: 1. The calibration schedule of ESD Simulator is arranged to be finished before Apr. 30, 1999

2. The calibration interval of the above test instruments is 12 months.
And the calibrations are traceable to NML/ROC and NIST/USA.

3.3 LIMITS OF CONDUCTED AND RADIATED EMISSION

LIMIT OF RADIATED EMISSION OF EN 55022

FREQUENCY (MHz)	Class A (at 10m)	Class B (at 10m)
	dBuV/m	dBuV/m
30 - 230	40	30
230 - 1000	47	37

- Note: (1) The lower limit shall apply at the transition frequencies.
- (2) Emission level (dBuV/m) = 20 log Emission level (uV/m).
- (3) All emanation from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

LIMIT OF CONDUCTED EMISSION OF EN 55022

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 - 56	56 - 46
0.50 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

- Note: (1) The lower limit shall apply at the transition frequencies.
- (2) The limit decreases linearly with the logarithm of the frequency in the range 0.15 to 0.50 MHz
- (3) All emanation from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.



4. TEST RESULTS (EMISSION)

4.1 RADIO DISTURBANCE

Product Family Standard : EN 55022: 1994+A1: 1995+A2: 1997, Class A
Frequency Range : 0.15 - 30 MHz (Conducted Emission)
30 - 1000 MHz (Radiated Emission)
Input Voltage : 230 Vac, 50 Hz
Temperature : 21 degree C
Humidity : 73 %
Atmospheric Pressure : 1000 mbar

TEST RESULT	Remarks
PASS	Minimum passing margin of conducted emission: -8.6 dB at 0.287 MHz Minimum passing margin of radiated emission: -3.3 dB at 171.85 MHz

4.1.1 EUT OPERATION CONDITION

1. Turn on the power of all equipment.
2. Industrial PC (EUT) reads a test program to enable all functions.
3. Industrial PC (EUT) reads and writes messages from HDD and FDD.
4. Industrial PC (EUT) sends "H" messages to monitor and monitor displays "H" patterns on screen.
5. Industrial PC (EUT) sends "H" messages to modem.
6. Industrial PC (EUT) sends "H" messages to printer and the printer prints them on paper.
7. Repeat steps 2-7.



4.1.2 TEST DATA OF CONDUCTED EMISSION (A)

EUT: INDUSTRIAL COMPUTER

MODEL: IPC-623MB-300

MODE: 1

6 dB Band Width: 10 kHz

PHASE: LINE (L)

Freq.	Meter Reading [dB (uV)]					Limit		Margin	
[MHz]	Corr.	Reading Data		Total		[dB (uV)]		[dB (uV)]	
	Factor	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.195	0.2	43.0	-	43.2	-	79.0	66.0	-35.8	-
0.261	0.2	32.8	-	33.0	-	79.0	66.0	-46.0	-
1.347	0.3	38.4	-	38.7	-	73.0	60.0	-34.3	-
3.549	0.5	44.3	-	44.8	-	73.0	60.0	-28.2	-
7.577	0.7	51.8	-	52.5	-	73.0	60.0	-20.5	-
19.868	1.2	38.8	-	40.0	-	73.0	60.0	-33.0	-

Remarks:

1. "*": Undetectable
2. Q.P. and AV. are abbreviations of quasi-peak and average individually.
3. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
4. The emission levels of other frequencies were very low against the limit.
5. Margin value = Emission level - Limit value



TEST DATA OF CONDUCTED EMISSION (A)

EUT: INDUSTRIAL COMPUTER

MODEL: IPC-623MB-300

MODE: 1

6 dB Band Width: 10 kHz

PHASE: NEUTRAL (N)

Freq.	Meter Reading [dB (uV)]					Limit		Margin	
[MHz]	Corr.	Reading Data		Total		[dB (uV)]		[dB (uV)]	
	Factor	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.195	0.2	43.8	-	44.0	-	79.0	66.0	-35.0	-
0.261	0.2	34.7	-	34.9	-	79.0	66.0	-44.1	-
1.347	0.3	37.9	-	38.2	-	73.0	60.0	-34.8	-
3.549	0.4	45.1	-	45.5	-	73.0	60.0	-27.5	-
7.577	0.5	51.3	-	51.8	-	73.0	60.0	-21.2	-
19.868	0.8	36.2	-	37.0	-	73.0	60.0	-36.0	-

- Remarks:
1. "*": Undetectable
 2. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 3. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 4. The emission levels of other frequencies were very low against the limit.
 5. Margin value = Emission level - Limit value



4.1.3 TEST DATA OF CONDUCTED EMISSION (B)

EUT: INDUSTRIAL COMPUTER

MODEL: IPC-623MB-300X

MODE: 2

6 dB Band Width: 10 kHz

PHASE: LINE (L)

Freq.	Meter Reading [dB (uV)]					Limit		Margin	
[MHz]	Corr.	Reading Data		Total		[dB (uV)]		[dB (uV)]	
	Factor	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.189	0.2	41.8	-	42.0	-	79.0	66.0	-37.0	-
0.285	0.2	31.3	-	31.5	-	79.0	66.0	-47.5	-
0.570	0.2	27.9	-	28.1	-	73.0	60.0	-44.9	-
9.323	0.8	44.8	-	45.6	-	73.0	60.0	-27.4	-
13.049	0.9	40.2	-	41.1	-	73.0	60.0	-31.9	-
18.971	1.1	36.2	-	37.3	-	73.0	60.0	-35.7	-

- Remarks:
1. "*": Undetectable
 2. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 3. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 4. The emission levels of other frequencies were very low against the limit.
 5. Margin value = Emission level - Limit value



TEST DATA OF CONDUCTED EMISSION (B)

EUT: INDUSTRIAL COMPUTER

MODEL: IPC-623MB-300X

MODE: 2

6 dB Band Width: 10 kHz

PHASE: NEUTRAL (N)

Freq.	Meter Reading [dB (uV)]					Limit		Margin	
[MHz]	Corr.	Reading Data		Total		[dB (uV)]		[dB (uV)]	
	Factor	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.189	0.2	40.2	-	40.4	-	79.0	66.0	-38.6	-
0.285	0.2	31.2	-	31.4	-	79.0	66.0	-47.6	-
0.570	0.2	26.8	-	27.0	-	73.0	60.0	-46.0	-
9.323	0.6	45.2	-	45.8	-	73.0	60.0	-27.2	-
13.049	0.65	39.1	-	39.8	-	73.0	60.0	-33.2	-
18.971	0.8	34.1	-	34.9	-	73.0	60.0	-38.1	-

Remarks:

1. "*": Undetectable
2. Q.P. and AV. are abbreviations of quasi-peak and average individually.
3. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
4. The emission levels of other frequencies were very low against the limit.
5. Margin value = Emission level - Limit value



4.1.4 TEST DATA OF CONDUCTED EMISSION (C)

EUT: INDUSTRIAL COMPUTER

MODEL: IPC-623P4-400

MODE: 3

6 dB Band Width: 10 kHz

PHASE: LINE (L)

Freq.	Meter Reading [dB (uV)]					Limit		Margin	
[MHz]	Corr.	Reading Data		Total		[dB (uV)]		[dB (uV)]	
	Factor	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.160	0.15	60.3	-	60.5	-	79.0	66.0	-18.5	-
0.287	0.2	68.6	57.2	68.8	57.4	79.0	66.0	-10.2	-8.6
0.432	0.2	67.5	55.4	67.7	55.6	79.0	66.0	-11.3	-10.4
0.479	0.2	62.9	-	63.1	-	79.0	66.0	-15.9	-
9.323	0.8	47.2	-	48.0	-	73.0	60.0	-25.0	-
28.616	1.5	41.8	-	43.3	-	73.0	60.0	-29.7	-

- Remarks:
1. "*": Undetectable
 2. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 3. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 4. The emission levels of other frequencies were very low against the limit.
 5. Margin value = Emission level - Limit value



TEST DATA OF CONDUCTED EMISSION (C)

EUT: INDUSTRIAL COMPUTER

MODEL: IPC-623P4-400

MODE: 3

6 dB Band Width: 10 kHz

PHASE: NEUTRAL (N)

Freq.	Meter Reading [dB (uV)]					Limit		Margin	
[MHz]	Corr.	Reading Data		Total		[dB (uV)]		[dB (uV)]	
	Factor	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.160	0.15	62.8	-	63.0	-	79.0	66.0	-16.0	-
0.287	0.2	68.7	57.2	68.9	57.4	79.0	66.0	-10.1	-8.6
0.432	0.2	67.5	55.6	67.7	55.8	79.0	66.0	-11.3	-10.2
0.479	0.25	63.5	-	63.8	-	79.0	66.0	-15.2	-
9.323	0.6	41.5	-	42.1	-	73.0	60.0	-30.9	-
28.616	1.1	22.9	-	24.0	-	73.0	60.0	-49.0	-

- Remarks:
1. "*": Undetectable
 2. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 3. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 4. The emission levels of other frequencies were very low against the limit.
 5. Margin value = Emission level - Limit value



4.1.5 TEST DATA OF CONDUCTED EMISSION (D)

EUT: INDUSTRIAL COMPUTER

MODEL: IPC-623P4-300R

MODE: 4

6 dB Band Width: 10 kHz

PHASE: LINE (L)

Freq.	Meter Reading [dB (uV)]					Limit		Margin	
[MHz]	Corr.	Reading Data		Total		[dB (uV)]		[dB (uV)]	
	Factor	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.165	0.15	54.8	-	55.0	-	79.0	66.0	-24.0	-
0.198	0.2	52.1	-	52.3	-	79.0	66.0	-26.7	-
0.366	0.2	45.3	-	45.5	-	79.0	66.0	-33.5	-
0.498	0.2	46.2	-	46.4	-	79.0	66.0	-32.6	-
9.323	0.8	44.9	-	45.7	-	73.0	60.0	-27.3	-
13.697	0.9	38.2	-	39.1	-	73.0	60.0	-33.9	-

- Remarks:
1. "*": Undetectable
 2. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 3. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 4. The emission levels of other frequencies were very low against the limit.
 5. Margin value = Emission level - Limit value



TEST DATA OF CONDUCTED EMISSION (D)

EUT: INDUSTRIAL COMPUTER

MODEL: IPC-623P4-300R

MODE: 4

6 dB Band Width: 10 kHz

PHASE: NEUTRAL (N)

Freq.	Meter Reading [dB (uV)]					Limit		Margin	
[MHz]	Corr.	Reading Data		Total		[dB (uV)]		[dB (uV)]	
	Factor	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.165	0.15	55.1	-	55.3	-	79.0	66.0	-23.7	-
0.198	0.2	51.2	-	51.4	-	79.0	66.0	-27.6	-
0.366	0.2	42.3	-	42.5	-	79.0	66.0	-36.5	-
0.498	0.2	44.8	-	45.0	-	79.0	66.0	-34.0	-
9.323	0.3	42.3	-	42.6	-	73.0	60.0	-30.4	-
13.697	0.65	39.1	-	39.8	-	73.0	60.0	-33.2	-

Remarks:

1. "*": Undetectable
2. Q.P. and AV. are abbreviations of quasi-peak and average individually.
3. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
4. The emission levels of other frequencies were very low against the limit.
5. Margin value = Emission level - Limit value



4.1.6 TEST DATA OF RADIATED EMISSION (A)

EUT: **INDUSTRIAL COMPUTER**

MODEL: **IPC-623MB-300**

MODE: **1**

ANT. POLARITY: **Horizontal**

DETECTOR FUNCTION: **Quasi-peak**

6 dB BANDWIDTH: **120 kHz**

FREQUENCY RANGE: **30-1000 MHz**

MEASURED DISTANCE: **10 M**

Frequency (MHz)	Correction Factor (dB)	Reading Data (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
146.10	13.1	13.8	26.9	40.0	-13.1
171.85	11.6	25.1	36.7	40.0	-3.3
197.15	12.4	13.1	25.5	40.0	-14.5
206.38	12.8	18.8	31.6	40.0	-8.4
223.10	13.6	15.5	29.1	40.0	-10.9
240.33	14.4	17.3	31.7	47.0	-15.3

REMARKS:

1. Emission level (dBuV/m) = Correction Factor (dB/m) + Meter Reading (dBuV).
2. Correction Factor (dB) = Ant. Factor (dB)+Cable loss (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level - Limit value



TEST DATA OF RADIATED EMISSION (A)

EUT: INDUSTRIAL COMPUTER

MODEL: IPC-623MB-300

MODE: 1

ANT. POLARITY: Vertical

DETECTOR FUNCTION: Quasi-peak

6 dB BANDWIDTH: 120 kHz

FREQUENCY RANGE: 30-1000 MHz

MEASURED DISTANCE: 10 M

Frequency (MHz)	Correction Factor (dB)	Reading Data (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
146.10	12.7	14.8	27.5	40.0	-12.5
171.85	11.5	24.7	36.2	40.0	-3.8
197.25	12.1	17.7	29.8	40.0	-10.2
200.53	12.2	19.0	31.2	40.0	-8.8
206.08	12.5	19.0	31.5	40.0	-8.5
240.33	14.4	17.3	31.7	47.0	-15.3

- REMARKS:
1. Emission level (dBuV/m) = Correction Factor (dB/m) + Meter Reading (dBuV).
 2. Correction Factor (dB) = Ant. Factor (dB)+Cable loss (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level - Limit value



4.1.7 TEST DATA OF RADIATED EMISSION (B)

EUT: **INDUSTRIAL COMPUTER**

MODEL: **IPC-623MB-300X**

MODE: **2**

ANT. POLARITY: **Horizontal**

DETECTOR FUNCTION: **Quasi-peak**

6 dB BANDWIDTH: **120 kHz**

FREQUENCY RANGE: **30-1000 MHz**

MEASURED DISTANCE: **10 M**

Frequency (MHz)	Correction Factor (dB)	Reading Data (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
48.00	11.1	18.0	29.1	40.0	-10.9
120.20	13.7	12.2	25.9	40.0	-14.1
144.10	13.3	15.5	28.8	40.0	-11.2
192.15	12.2	21.1	33.3	40.0	-6.7
203.15	12.6	16.4	29.0	40.0	-11.0
209.00	12.9	20.6	33.5	40.0	-6.5
220.33	13.4	18.3	31.7	40.0	-8.3
596.35	24.3	13.6	37.9	47.0	-9.1

REMARKS:

1. Emission level (dBuV/m) = Correction Factor (dB/m) + Meter Reading (dBuV).
2. Correction Factor (dB) = Ant. Factor (dB)+Cable loss (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level - Limit value



TEST DATA OF RADIATED EMISSION (B)

EUT: INDUSTRIAL COMPUTER

MODEL: IPC-623MB-300X

MODE: 2

ANT. POLARITY: Vertical

DETECTOR FUNCTION: Quasi-peak

6 dB BANDWIDTH: 120 kHz

FREQUENCY RANGE: 30-1000 MHz

MEASURED DISTANCE: 10 M

Frequency (MHz)	Correction Factor (dB)	Reading Data (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
47.99	9.9	26.0	35.9	40.0	-4.1
120.12	13.6	19.6	33.2	40.0	-6.8
144.10	13.0	18.0	31.0	40.0	-9.0
168.10	11.4	16.3	27.7	40.0	-12.3
192.05	12.0	19.3	31.3	40.0	-8.7
208.93	12.7	16.2	28.9	40.0	-11.1
220.18	13.3	19.6	32.9	40.0	-7.1
596.35	23.3	13.1	36.4	47.0	-10.6

REMARKS:

1. Emission level (dBuV/m) = Correction Factor (dB/m) + Meter Reading (dBuV).
2. Correction Factor (dB) = Ant. Factor (dB)+Cable loss (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level - Limit value



4.1.8 TEST DATA OF RADIATED EMISSION (C)

EUT: **INDUSTRIAL COMPUTER**

MODEL: **IPC-623P4-400**

MODE: **3**

ANT. POLARITY: **Horizontal**

DETECTOR FUNCTION: **Quasi-peak**

6 dB BANDWIDTH: **120 kHz**

FREQUENCY RANGE: **30-1000 MHz**

MEASURED DISTANCE: **10 M**

Frequency (MHz)	Correction Factor (dB)	Reading Data (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
87.00	8.8	12.6	21.4	40.0	-18.6
171.85	11.6	14.9	26.5	40.0	-13.5
203.08	12.6	13.8	26.4	40.0	-13.6
206.30	12.8	13.4	26.2	40.0	-13.8
214.63	13.2	13.9	27.1	40.0	-12.9
220.40	13.5	15.1	28.6	40.0	-11.4
386.70	19.5	13.6	33.1	47.0	-13.9
515.63	23.1	10.3	33.4	47.0	-13.6

REMARKS:

1. Emission level (dBuV/m) = Correction Factor (dB/m) + Meter Reading (dBuV).
2. Correction Factor (dB) = Ant. Factor (dB)+Cable loss (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level - Limit value



TEST DATA OF RADIATED EMISSION (C)

EUT: **INDUSTRIAL COMPUTER**

MODEL: **IPC-623P4-400**

MODE: **3**

ANT. POLARITY: **Vertical**

DETECTOR FUNCTION: **Quasi-peak**

6 dB BANDWIDTH: **120** kHz

FREQUENCY RANGE: **30-1000** MHz

MEASURED DISTANCE: **10** M

Frequency (MHz)	Correction Factor (dB)	Reading Data (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
60.08	6.8	26.3	33.1	40.0	-6.9
87.01	8.2	17.3	25.5	40.0	-14.5
116.01	13.0	20.3	33.3	40.0	-6.7
171.84	11.5	20.7	32.2	40.0	-7.8
203.00	12.3	17.5	29.8	40.0	-10.2
214.55	13.0	15.7	28.7	40.0	-11.3
229.10	13.8	12.8	26.6	40.0	-13.4
514.70	22.9	11.4	34.3	47.0	-12.7

REMARKS:

1. Emission level (dBuV/m) = Correction Factor (dB/m) + Meter Reading (dBuV).
2. Correction Factor (dB) = Ant. Factor (dB)+Cable loss (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level - Limit value



4.1.9 TEST DATA OF RADIATED EMISSION (D)

EUT: **INDUSTRIAL COMPUTER**

MODEL: **IPC-623P4-300R**

MODE: **4**

ANT. POLARITY: **Horizontal**

DETECTOR FUNCTION: **Quasi-peak**

6 dB BANDWIDTH: **120 kHz**

FREQUENCY RANGE: **30-1000 MHz**

MEASURED DISTANCE: **10 M**

Frequency (MHz)	Correction Factor (dB)	Reading Data (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
167.04	11.5	21.0	32.5	40.0	-7.5
169.38	11.5	18.9	30.4	40.0	-9.6
175.03	11.6	22.1	33.7	40.0	-6.3
200.45	12.5	22.7	35.2	40.0	-4.8
209.00	12.9	16.6	29.5	40.0	-10.5
267.27	15.0	12.0	27.0	47.0	-20.0
534.55	23.4	13.2	36.6	47.0	-10.4

REMARKS:

1. Emission level (dBuV/m) = Correction Factor (dB/m) + Meter Reading (dBuV).
2. Correction Factor (dB) = Ant. Factor (dB)+Cable loss (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level - Limit value



TEST DATA OF RADIATED EMISSION (D)

EUT: **INDUSTRIAL COMPUTER**

MODEL: **IPC-623P4-300R**

MODE: **4**

ANT. POLARITY: Vertical

DETECTOR FUNCTION: Quasi-peak

6 dB BANDWIDTH: 120 kHz

FREQUENCY RANGE: 30-1000 MHz

MEASURED DISTANCE: 10 M

Frequency (MHz)	Correction Factor (dB)	Reading Data (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
167.04	11.3	21.4	32.7	40.0	-7.3
169.37	11.4	20.4	31.8	40.0	-8.2
175.01	11.6	19.8	31.4	40.0	-8.6
180.65	11.7	16.6	28.3	40.0	-11.7
200.40	12.2	23.8	36.0	40.0	-4.0
214.63	13.0	12.2	25.2	40.0	-14.8
267.28	15.5	16.5	32.0	47.0	-15.0
701.55	25.7	6.1	31.8	47.0	-15.2

REMARKS:

1. Emission level (dBuV/m) = Correction Factor (dB/m)
+ Meter Reading (dBuV).
2. Correction Factor (dB) = Ant. Factor (dB)+Cable loss (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level - Limit value



4.2 DISTURBANCE IN SUPPLY SYSTEM

Product Family Standard: EN 61000-3-2, Class A (for mode 2 & 3)
EN 60555-2 (for mode 4)

Input Voltage : 230Vac, 50Hz

Temperature : 21 degree C

Humidity : 53 %

Atmospheric Pressure : 1000 mbar

TEST RESULT	Remarks
PASS	MODE 2
PASS	MODE 3
PASS	MODE 4

Note: MODE 2 & 3 meet the requirement of Class A limit. Class A or Class D is classified by test instruments automatically.

4.2.1 EUT OPERATION CONDITION

Same as item 4.1.1.



4.2.2 MEASUREMENT DATA OF HARMONICS TEST (A)

EUT: **INDUSTRIAL COMPUTER**

MODE: **2**

TEST STANDARD: **EN 61000-3-2, Class A**

MODEL: **IPC-623MB-300X**

Fundamental Voltage : 229.756 Vrms

Amperes : 0.467 Arms

Frequency : 50 Hz

Power Consumption : 54.835 W

Harm. Order	Reading Data (A)	Limit (A)
1	-	-
3	0.21	2.30
5	0.20	1.14
7	0.17	0.77
9	0.14	0.40
11	0.11	0.33
13	0.08	0.21
15	0.06	0.15
17	0.03	0.13
19	0.02	0.12
21	0.01	0.11
23	0.01	0.10
25	0.01	0.09
27	0.01	0.08
29	0.01	0.08
31	0.01	0.07
33	0.01	0.07
35	0.01	0.06
37	0.01	0.06
39	0.01	0.06

Harm. Order	Reading Data (A)	Limit (A)
2	0.00	1.08
4	0.00	0.43
6	0.00	0.30
8	0.00	0.23
10	0.00	0.18
12	0.00	0.15
14	0.00	0.13
16	0.00	0.11
18	0.00	0.10
20	0.00	0.09
22	0.00	0.08
24	0.00	0.08
26	0.00	0.07
28	0.00	0.07
30	0.00	0.06
32	0.00	0.06
34	0.00	0.05
36	0.00	0.05
38	0.00	0.05
40	0.00	0.05

Note: Steady state values on AC mains are recorded in the table.



4.2.3 MEASUREMENT DATA OF HARMONICS TEST (B)

EUT: **INDUSTRIAL COMPUTER**

MODE: **3**

TEST STANDARD: **EN 61000-3-2, Class A**

MODEL: **IPC-6234P4-400**

Fundamental Voltage : 229.715 Vrms

Amperes : 0.542 Arms

Frequency : 50 Hz

Power Consumption : 61.663 W

Harm. Order	Reading Data (A)	Limit (A)
1	-	-
3	0.25	2.30
5	0.23	1.14
7	0.20	0.77
9	0.17	0.40
11	0.14	0.33
13	0.10	0.21
15	0.07	0.15
17	0.04	0.13
19	0.02	0.12
21	0.01	0.11
23	0.02	0.10
25	0.02	0.09
27	0.02	0.08
29	0.02	0.08
31	0.01	0.07
33	0.01	0.07
35	0.00	0.06
37	0.01	0.06
39	0.01	0.06

Harm. Order	Reading Data (A)	Limit (A)
2	0.00	1.08
4	0.00	0.43
6	0.00	0.30
8	0.00	0.23
10	0.00	0.18
12	0.00	0.15
14	0.00	0.13
16	0.00	0.11
18	0.02	0.10
20	0.00	0.09
22	0.00	0.08
24	0.00	0.08
26	0.00	0.07
28	0.00	0.07
30	0.00	0.06
32	0.00	0.06
34	0.00	0.05
36	0.00	0.05
38	0.00	0.05
40	0.00	0.05

Note: Steady state values on AC mains are recorded in the table.



4.2.4 MEASUREMENT DATA OF HARMONICS TEST (C)

EUT: **INDUSTRIAL COMPUTER**

MODE: **4**

TEST STANDARD: **EN 60555-2**

MODEL: **IPC-623P4-300R**

Fundamental Voltage : 229.771 Vrms

Amperes : 0.732 Arms

Frequency : 50 Hz

Power Consumption : 78.024 W

Harm. Order	Reading Data (A)	Limit (A)
1	-	-
3	0.32	2.30
5	0.30	1.14
7	0.27	0.77
9	0.24	0.40
11	0.20	0.33
13	0.16	0.21
15	0.13	0.15
17	0.09	0.13
19	0.06	0.12
21	0.04	0.11
23	0.02	0.10
25	0.01	0.09
27	0.01	0.08
29	0.01	0.08
31	0.01	0.07
33	0.01	0.07
35	0.02	0.06
37	0.01	0.06
39	0.01	0.06

Harm. Order	Reading Data (A)	Limit (A)
2	0.00	1.08
4	0.00	0.43
6	0.01	0.30
8	0.00	0.23
10	0.00	0.18
12	0.00	0.15
14	0.00	0.13
16	0.00	0.11
18	0.00	0.10
20	0.00	0.09
22	0.00	0.08
24	0.00	0.08
26	0.00	0.07
28	0.00	0.07
30	0.00	0.06
32	0.01	0.06
34	0.02	0.05
36	0.00	0.05
38	0.00	0.05
40	0.00	0.05

Note: Steady state values on AC mains are recorded in the table.



4.3 VOLTAGE FLUCTUATIONS AND FLICKER

Basic Standard : EN 61000-3-3
Input Voltage : 230Vac, 50Hz
Temperature : 21 degree C
Humidity : 53 %
Atmospheric Pressure : 1000 mbar

TEST RESULT	Remarks
PASS	MODE 1
PASS	MODE 2
PASS	MODE 3
PASS	MODE 4

Note: The measured reading is too low against the limit.

4.3.1 EUT OPERATION CONDITION

Same as item 4.1.1.



4.3.2 TEST DATA OF VOLTAGE FLUCTUATIONS AND FLICKER (A)

EUT: INDUSTRIAL COMPUTER

MODEL: IPC-623MB-300

MODE: 1

Input Voltage : 229.844 Vrms

Input Amperes : 0.642 Arms

Power Factor : 0.376

Power Frequency: 50 Hz

Observation period (Tp): 2 hour

The measured data are too low against the limit and therefore they are not reported.



4.3.3 TEST DATA OF VOLTAGE FLUCTUATIONS AND FLICKER (B)

EUT: INDUSTRIAL COMPUTER

MODEL: IPC-623MB-300X

MODE: 2

Input Voltage : 229.756 Vrms

Input Amperes : 0.467 Arms

Power Factor : 0.511

Power Frequency: 50 Hz

Observation period (Tp): 2 hour

The measured data are too low against the limit and therefore they are not reported.



4.3.4 TEST DATA OF VOLTAGE FLUCTUATIONS AND FLICKER (C)

EUT: INDUSTRIAL COMPUTER

MODEL: IPC-6234P4-400

MODE: 3

Input Voltage : 229.715 Vrms

Input Amperes : 0.542 Arms

Power Factor : 0.495

Power Frequency: 50 Hz

Observation period (Tp): 2 hour

The measured data are too low against the limit and therefore they are not reported.



4.3.5 TEST DATA OF VOLTAGE FLUCTUATIONS AND FLICKER (D)

EUT: **INDUSTRIAL COMPUTER**

MODEL: **IPC-623P4-300R**

MODE: **4**

Input Voltage : 229.771 Vrms

Input Amperes : 0.732 Arms

Power Factor : 0.464

Power Frequency: 50 Hz

Observation period (Tp): 2 hour

The measured data are too low against the limit and therefore they are not reported.



5. TEST RESULTS (IMMUNITY)

5.1 GENERAL DESCRIPTION

Generic Standard	:	EN 50082-2: 1995	
Basic Standard	:	EN 61000-4-2	(Electrostatic Discharge, ESD, 8kV air discharge, 4kV Contact discharge, Performance Criterion B)
Specification and Performance Criteria		EN 61000-4-3	(Radio-Frequency Electromagnetic Field Susceptibility Test, RS, 80-1000 MHz, 10V/m, 80% AM (1kHz), Performance Criterion A)
		EN 61000-4-4	(Electrical Fast Transient/Burst, EFT, Power line: 2kV, Signal line: 1kV, Performance Criterion B)
		EN 61000-4-6	(Conducted Radio Frequency Disturbances Test, CS, 0.15-80 MHz, 10V/m, 80% AM, 1kHz, Performance Criterion A)
		EN 61000-4-8	(Power Frequency Magnetic Field Test, 50 Hz, 30A/m, Performance Criterion A)
		ENV 50204	(Radio-Frequency Electromagnetic Field, Pulse modulated, 900+/-5 MHz, 10V/m, 50 % duty cycle, Rep. Frequency 200 Hz, Performance Criterion A)
Input Voltage	:	230 Vac, 50 Hz	
Temperature	:	21 degree C	
Humidity	:	53 %	
Atmospheric Pressure	:	1000 mbar	

5.2 PERFORMANCE CRITERIA DESCRIPTION

- Criterion A - The apparatus shall continue to operate as intended. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended.
- Criterion B - The apparatus shall continue to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended.
- Criterion C - Temporary loss of function is allowed, provided the function is self-recoverable or can be restored by the operation of the controls.

5.3 EUT OPERATION CONDITION

Same as item 4.1.1.



5.5 TEST RESULT OF RADIATED ELECTROMAGNETIC FIELDS (RS)

Basic Standard : EN 61000-4-3
Frequency range : 80 MHz - 1000 MHz
Field strength : 10 V/m
Modulation : 1kHz Sine Wave, 80%, AM Modulation
Frequency step : 1 % of fundamental
Polarity of Antenna : Horizontal and Vertical
Test distance : 3 m

Test Result		Remarks
Criterion A	PASS	MODE 1
Criterion A	PASS	MODE 2
Criterion A	PASS	MODE 3
Criterion A	PASS	MODE 4

Note: Four sides of EUT are verified separately.

Description of test result:

There was no change compared with initial operation during the test.



5.6 TEST RESULT OF ELECTRICAL FAST TRANSIENT (EFT)

Basic Standard : EN 61000-4-4
Test Voltage : Power Line - 2 kV
Signal/Control Line - NA
Polarity : Positive/Negative
Impulse Frequency : 5 kHz
Tr / Tn : 5/50 ns
Burst Duration : 15 ms
Burst Period : 300 ms
Test Duration : Not less than 1 min.

Test Result		Remarks
Criterion B	PASS	MODE 1
Criterion B	PASS	MODE 2
Criterion B	PASS	MODE 3
Criterion A	PASS	MODE 4

OBSERVATION DESCRIPTION (MODE 1, 2 & 3)

Test Point	Polarity	Test Level (kV)	Result
L1	+/-	2	Note 2
L2	+/-	2	Note 2
GND	+/-	2	Note 2

OBSERVATION DESCRIPTION (MODE 4)

Test Point	Polarity	Test Level (kV)	Result
L1	+/-	2	Note 1
L2	+/-	2	Note 1
GND	+/-	2	Note 1

Description of test result:

Note 1: There was no change compared with initial operation during the test.

Note 2: Mouse and keyboard loose their functions during the test and recoverable only after they are reconnected to PC.



5.7 TEST RESULT OF CONDUCTED RADIO FREQUENCY DISTURBANCES (CS)

Basic Standard : EN 61000-4-6
Frequency range : 0.15 MHz - 80 MHz
Field strength : 10 V/m
Modulation : 1kHz Sine Wave, 80%, AM Modulation
Frequency step : 1 % of fundamental
Coupled cable : Power Mains, Unshielded
Coupling device : CDN-M3 (3 wires)

Test Result		Remarks
Criterion A	PASS	MODE 1
Criterion A	PASS	MODE 2
Criterion A	PASS	MODE 3
Criterion A	PASS	MODE 4

OBSERVATION DESCRIPTION

There was no change compared with initial operation during the test.



5.8 TEST RESULT OF POWER FREQUENCY MAGNETIC FIELD

Basic Standard : EN 61000-4-8
Frequency range : 50Hz
Field strength : 30 A/m
Observation Time : 1 minute
Inductance coil : Rectangular type, 1mx1m

Test Result		Remarks
Criterion A	PASS	MODE 1
Criterion A	PASS	MODE 2
Criterion A	PASS	MODE 3
Criterion A	PASS	MODE 4

OBSERVATION DESCRIPTION

There was no change compared with initial operation during the test.



5.9 TEST RESULT OF RADIO-FREQUENCY ELECTROMAGNETIC FIELD, PULSE MODULATED

Basic Standard : ENV 50204
Frequency range : 900 +/- 5 MHz
Field strength : 10 V/m
Modulation : 200Hz, Square Wave, 50% Duty Cycle
Dwell Time : 30 second
Polarity of Antenna : Horizontal and Vertical
Test distance : 3 m

Test Result		Remarks
Criterion A	PASS	MODE 1
Criterion A	PASS	MODE 2
Criterion A	PASS	MODE 3
Criterion A	PASS	MODE 4

Note: Four sides of EUT are verified separately.

OBSERVATION DESCRIPTION

There was no change compared with initial operation during the test.

6. PHOTOGRAPHS OF THE TEST CONFIGURATION


CONDUCTED EMISSION TEST (MODE 1)



CONDUCTED EMISSION TEST (Mode 2)



CONDUCTED EMISSION TEST (MODE 3)




CONDUCTED EMISSION TEST (MODE 4)



RADIATED EMISSION TEST (MODE 1)




RADIATED EMISSION TEST (MODE 2)



RADIATED EMISSION TEST (MODE 3)



RADIATED EMISSION TEST (MODE 4)



VOLTAGE FLUCTUATIONS AND FLICKER TEST (MODE 1)



HARMONICS EMISSION TEST & VOLTAGE FLUCTUATIONS AND FLICKER TEST (MODE 2)



HARMONICS EMISSION TEST & VOLTAGE FLUCTUATIONS AND FLICKER TEST (MODE 3)



HARMONICS EMISSION TEST & VOLTAGE FLUCTUATIONS AND FLICKER TEST (MODE 4)



ESD TEST (MODE 1)



ESD TEST (MODE 2)



ESD TEST (MODE 3)



ESD TEST (MODE 4)




RS TEST & PULSE MODULATION TEST (MODE 1)



RS TEST & PULSE MODULATION TEST (MODE 2)



RS TEST & PULSE MODULATION TEST (MODE 3)



RS TEST & PULSE MODULATION TEST (MODE 4)



EFT TEST (MODE 1)



EFT TEST (MODE 2)



EFT TEST (MODE 3)



EFT TEST (MODE 4)



CONDUCTED SUSCEPTIBILITY TEST (MODE 1)



CONDUCTED SUSCEPTIBILITY TEST (MODE 2)




CONDUCTED SUSCEPTIBILITY TEST (MODE 3)



CONDUCTED SUSCEPTIBILITY TEST (MODE 4)




MAGNETIC TEST (MODE 1)



MAGNETIC TEST (MODE 2)



MAGNETIC TEST (MODE 3)



MAGNETIC TEST (MODE 4)





7. APPENDIX - INFORMATION OF THE TESTING LABORATORY

Information of the testing laboratory

We, ADT Corp., are founded in 1988, to provide our best service in EMC and Safety consultation. Our laboratory is accredited by the following approval agencies according to ISO/IEC Guide 25 or EN 45001:

- | | |
|---------------|--------------------------------------|
| ● USA | FCC, UL, NVLAP |
| ● Germany | TUV Rheinland
TUV Product Service |
| ● Japan | VCCI |
| ● New Zealand | RFS |
| ● Norway | NEMKO, DNV |
| ● U.K. | INCHCAPE, SGS |
| ● R.O.C. | BSMI |

Enclosed please find some certificates of our laboratory obtained from approval agencies. If you have any comments, please feel free to contact us with the following:

Lin Kou EMC Lab.:

Tel: 886-2-26032180

Fax: 886-2-26022943

Hsin Chu EMC Lab:

Tel: 886-35-935343

Fax: 886-35-935342

Lin Kou Safety Lab.:

Tel: 886-2-26093195

Fax: 886-2-26093184

Design Center:

Tel: 886-2-26093195

Fax: 886-2-26093184

E-mail: service@mail.adt.com.tw

<http://www.adt.com.tw>