



EMC

TEST REPORT

REPORT NO. : CE88042306

MODEL NO. : PCA-6168 SERIES

DATE OF TEST : April 23 ~ 30, 1999

PREPARED FOR : ADVANTECH CO., LTD.

ADDRESS : FL. 4, NO. 108-3, MING-CHUAN ROAD,
SHING-TIEN CITY TAIPEI HSIEN, TAIWAN

PREPARED BY: ADVANCE DATA TECHNOLOGY CORPORATION



Accredited Laboratory

11F, NO.1, SEC.4, NAN-KING EAST RD.,
TAIPEI, TAIWAN, R.O.C.

This test report consists of 30 pages in total. It may be duplicated completely for legal use with the allowance of the applicant. It shall not be reproduced except in full, without the written approval of our laboratory. It should not be used by the client to claim product endorsement by NVLAP or any agency of the U.S. government. The test result in the report only applies to the tested sample.



TABLE OF CONTENTS

1. CERTIFICATION	3
2. GENERAL INFORMATION	4
2.1 GENERAL DESCRIPTION OF EUT	4
2.2 GENERAL DESCRIPTION OF APPLIED STANDARD	4
2.3 DESCRIPTION OF SUPPORT UNITS	5
2.4 TEST SETUP	6
3. TEST INSTRUMENTS	7
3.1 TEST INSTRUMENTS (EMISSION)	7
3.2 TEST INSTRUMENTS (IMMUNITY)	8
3.3 LIMITS OF CONDUCTED AND RADIATED EMISSION	9
4. TEST RESULTS (EMISSION)	10
4.1 RADIO DISTURBANCE	10
4.2 EUT OPERATION CONDITION	10
4.3 TEST DATA OF CONDUCTED EMISSION	11
4.4 TEST DATA OF RADIATED EMISSION	13
5. TEST RESULTS (IMMUNITY)	15
5.1 GENERAL DESCRIPTION	15
5.2 PERFORMANCE CRITERIA DESCRIPTION	15
5.3 EUT OPERATION CONDITION	15
5.4 TEST RESULT OF ELECTROSTATIC DISCHARGE (ESD)	16
5.5 TEST RESULT OF RADIATED ELECTROMAGNETIC FIELDS (RS)	17
5.6 TEST RESULT OF ELECTRICAL FAST TRANSIENT (EFT)	18
5.7 TEST RESULT OF CONDUCTED RADIO FREQUENCY DISTURBANCES (CS)	19
5.8 TEST RESULT OF POWER FREQUENCY MAGNETIC FIELD	20
5.9 TEST RESULT OF RADIO-FREQUENCY ELECTROMAGNETIC	21
6. PHOTOGRAPHS OF THE TEST CONFIGURATION	22
7. APPENDIX - INFORMATION OF THE TESTING LABORATORY	30



1. CERTIFICATION

Issue date: May 6, 1999

Product : CPU BOARD
Trade Name : ADVANTECH
Model No. : PCA-6168 SERIES
Applicant : ADVANTECH CO., LTD.
Standard : EN 55022: 1994+A1: 1995+A2: 1997, **EN 50082-2: 1995**
Class A EN 61000-4-2: 1995
EN 61000-4-3: 1996
EN 61000-4-4: 1995
EN 61000-4-6: 1996
EN 61000-4-8: 1993
ENV 50204: 1995

We hereby certify that one sample of the designation has been tested in our facility from April. 23 to 30, 1999. The test record, data evaluation and Equipment Under Test (EUT) configurations represent herein are true and accurate representation of the measurements of the sample's EMC characteristics under the conditions herein specified.

TESTED BY : _____ , DATE: _____
(Emission) (Kent Chen)

TESTED BY : _____ , DATE: _____
(Immunity) (S.S. Wang)

CHECKED BY : _____ , DATE: _____
(Stacy Chang)

APPROVED BY : _____ , DATE: _____
(Mike Su)

ADVANCE DATA TECHNOLOGY CORPORATION



Accredited Laboratory



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Product : CPU BOARD
Model No. : PCA-6168 SERIES
Power Supply Type : Switching (from PC)
Power Cord : Non-shielded (1.8 m)

Note: The EUT was tested under the following configuration:

ITEM	BRAND	MODEL	REMARK
CPU	INTEL	CELERON 366 MHz	-
CHASSIS	ADVANTECH	IPC-610	-
BACKPLANE	ADVANTECH	PCA-6113, B101 version	-
VGA CARD	-	-	ON BOARD (1280x1024)
SPS	SKYNET	ADT-925C	260W
FDD	TEAC	FD-235HF	-
HDD	QUANTUM	3.5 SERIES	-
CPU BOARD	ADVANTECH	PCA-6168 SERIES, A102 version	-

The video resolution of 1280 x 1024 was used during the test.

For more detailed features description, please refer to manufacturer' s specification or User's Manual.

2.2 GENERAL DESCRIPTION OF APPLIED STANDARD

According to the manufacturer' s request, the EUT was tested with the requirements of the following standards:

EN 55022: 1994+A1: 1995+A2: 1997, Class A

EN 50082-2: 1995
EN 61000-4-2: 1995
EN 61000-4-3: 1996
EN 61000-4-4: 1995
EN 61000-4-6: 1996
EN 61000-4-8: 1993
ENV 50204: 1995

All tests are performed and recorded as per above standards.

2.3 DESCRIPTION OF SUPPORT UNITS

The EUT was installed into a system and tested together with necessary accessories or support units. The following support units or accessories are used to form representative test configuration during the tests.

FOR EMISSION TEST

No	Product	Brand	Model No.	Serial No.	I/O Cable
1	COLOR MONITOR	ADI	PD-959	730020U00100292	Shielded Signal (1.8m) Nonshielded Power (1.8m)
2	MODEM	DATATRONICS	1200CK	07-503069	Shielded Signal (1.0m) Nonshielded Power (1.2m)
3	PRINTER	HP	2225C+	3208S05355	Shielded Signal (1.2m) Nonshielded Power (1.2m)
4	USB KEYBOARD	BTC	7932	174250046	Shielded Signal (1.7m)
5	USB MOUSE	DEXIN	A2U800A	71001824	Shielded Signal (1.5m)
6	MOUSE	LOGITECH	M-M30	LTR53500777	Shielded Signal (1.9m)
7	KEYBOARD	FORWARD	FDA-104GA	FDKB8110123	Shielded Signal (1.4m)
8	PERSONAL COMPUTER	IBM	6560-T7T	9983708	Nonshielded Power (1.8m)
9	MONITOR	ACER	7134T	M500233562	Shielded Signal (1.5m) Nonshielded Power (1.8m)
10	KEYBOARD	HP	C3758A	K101087	Shielded Signal (1.5m)
11	MOUSE	DEXIN	A2P800A	80110011	Shielded Signal (1.8m)
12	LAN CARD	INTEL	S82555	00A0C9A6CB525271	NA

Note: 1. Support units 4 & 5 were connected to the USB ports of PC system.

2. Support units 1-7 were set up as the SERVER PC system and communicated with support units 8-12 which acted as WORKSTATION and partners of communication system via a UTP cable (10m).



FOR IMMUNITY TEST

No	Product	Brand	Model No.	Serial No.	I/O Cable
1	COLOR MONITOR	ADI	937G	649015T00102094A	Shielded Signal (1.5m) Nonshielded Power (1.8m)
2	MODEM	GVC	F-1128V1R6	96-191-113003	Shielded Signal (1.25m) Nonshielded Power (1.5m)
3	PRINTER	HP	C2145A	SG59N16035	Shielded Signal (1.5m) Nonshielded Power (1.8m)
4	MOUSE	DEXIN	A2R800A	80110026	Shielded Signal (1.5m)
5	KEYBOARD	HP	C3758A	CIGEO03633	Shielded Signal (1.8m)
6	CCD CAMERA 2X	COMPAQ	YC72-CPQ	G06CC0A7AEB22Y G06CC0A7AEB20J	Shielded Signal (2.0m)
7	PERSONAL COMPUTER	IBM	6587-T7T	90A54WX	Nonshielded Power (1.8m)
8	MONITOR	ACTION	0951	NA	Shielded Signal (1.5m) Nonshielded Power (1.5m)
9	KEYBOARD	ACER	6311	K6355122516	Shielded Signal (1.8m)
10	MOUSE	DEXIN	A2P800A	80102121	Shielded Signal (1.5m)
11	LAN CARD	INTEL	S82555	00A0C9659E5C17713	NA

Note: 1. Support units 6 were connected to the USB ports of PC system.

2. Support units 1-6 were set up as the SERVER PC system and communicated with support units 7-11 which acted as WORKSTATION and partners of communication system via a UTP cable (10m).

2.4 TEST SETUP

Please refer to the photos of test configuration in Item 6.



3. TEST INSTRUMENTS

3.1 TEST INSTRUMENTS (EMISSION)

CONDUCTED EMISSION MEASUREMENT

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
ROHDE & SCHWARZ Test Receiver	ESH3	893495/006	July 15, 1999
ROHDE & SCHWARZ Spectrum Monitor	EZM	893787/013	July 16, 1999
ROHDE & SCHWARZ Artificial Mains Network	ESH3-Z5	839135/006	July 14, 1999
EMCO-L.I.S.N.	3825/2	9204-1964	July 14, 1999
Shielded Room	Site 2	ADT-C02	NA

Note: 1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per NAMAS document NIS81.

2. The calibration interval of the above test instruments is 12 months.

And the calibrations are traceable to NML/ROC and NIST/USA.

RADIATED EMISSION MEASUREMENT

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
HP Spectrum Analyzer	8594A	3144A00308	Sept. 3, 1999
HP Preamplifier	8447D	2944A08119	July 20, 1999
HP Preamplifier	8347A	3307A01088	Sept. 9, 1999
ROHDE & SCHWARZ TEST RECEIVER	ESVP	893496/030	July 15, 1999
SCHWARZBECK Tunable Dipole Antenna	VHA 9103 UHA 9105	E101051 E101055	Nov. 25, 1999
CHASE Bilog Antenna	CBL6112A	2329	Sept. 19, 1999
EMCO Double Ridged Guide Antenna	3115	9312-4192	April 5, 2000
EMCO Turn Table	1060	1195	NA
EMCO Tower	1051	1163	NA
Open Field Test Site	Site 2	ADT-R02	Sept. 18, 1999

Note: 1. The measurement uncertainty is less than +/- 3dB, which is calculated as per NAMAS document NIS81.

2. The calibration interval of the above test instruments is 12 months.

And the calibrations are traceable to NML/ROC and NIST/USA.



3.2 TEST INSTRUMENTS (IMMUNITY)

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
KeyTek, ESD Test System	2000	9105240/41	Aug. 9, 1999
KeyTek, ESD Simulator	MZ-15/EC	92022232	April 14, 2000
KeyTek, EFT Generator	CE-40	9508257	Sept. 8, 1999
KeyTek, Capacitive Clamp	CE-40-CCL	9508259	Sept. 8, 1999
ROHDE & SCHWARZ Signal Generator	SMY01	840490/009	Sept. 30, 1999
KALMUS Power Amplifier	LA1000V	091995-1	N/A
KALMUS Power Amplifier	757LC	091995-2	N/A
HOLADAY Field Probe	HI-4422	89915	Oct. 27, 1999
EMCO BiconiLog Antenna	3141	1001	N/A
FCC Coupling Decoupling Network	FCC-801-M3-25	48	N/A
FCC Coupling Decoupling Network	FCC-801-M2-25	20	N/A
FISCHER CUSTOM COMMUNICATIONS EM Injection Clamp	FCC-203I	50	N/A
FCC Coupling Decoupling Network	FCC-801-M1-25	17	N/A
BOONTON RF Voltage Meter	9200B	331801AE	Dec. 17, 1999
COMTEST Compact Full Anechoic Chamber (7x3x3 m)	CFAC	ADT-S01	Aug. 4, 1999
HAEFELY Magnetic Field Tester	MAG 100.1	083794-06	N/A
COMBINOVA Magnetic Field Meter	MFM10	224	Aug. 26, 1999

Note: The calibration interval of the above test instruments is 12 months.

And the calibrations are traceable to NML/ROC and NIST/USA.



3.3 LIMITS OF CONDUCTED AND RADIATED EMISSION

LIMIT OF RADIATED EMISSION OF EN 55022

FREQUENCY (MHz)	Class A (at 10m)	Class B (at 10m)
	dBuV/m	dBuV/m
30 - 230	40	30
230 - 1000	47	37

- Note: (1) The lower limit shall apply at the transition frequencies.
(2) Emission level (dBuV/m) = 20 log Emission level (uV/m).
(3) All emanation from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

LIMIT OF CONDUCTED EMISSION OF EN 55022

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)0	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 - 56	56 - 46
0.50 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

- Note: (1) The lower limit shall apply at the transition frequencies.
(2) The limit decreases linearly with the logarithm of the frequency in the range 0.15 to 0.50 MHz
(3) All emanation from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.



4. TEST RESULTS (EMISSION)

4.1 RADIO DISTURBANCE

Product Family Standard : EN 55022: 1994+A1: 1995+A2: 1997, Class A
Frequency Range : 0.15 - 30 MHz (Conducted Emission)
30 - 1000 MHz (Radiated Emission)
Input Voltage : 230 Vac, 50 Hz
Temperature : 23 degree C
Humidity : 67 %
Atmospheric Pressure : 998 mbar

TEST RESULT	Remarks
PASS	Minimum passing margin of conducted emission: -25.9 dB at 3.430 MHz Minimum passing margin of radiated emission: -4.0 dB at 434.36 MHz

4.2 EUT OPERATION CONDITION

1. Turn on the power of all equipment.
2. Industrial PC reads a test program to enable all functions.
3. Industrial PC reads and writes messages from HDD and FDD.
4. Industrial PC sends "H" messages to monitor and monitor displays "H" patterns on screen.
5. Industrial PC sends "H" messages to modem.
6. Industrial PC sends "H" messages to printer and the printer prints them on paper.
7. Repeat steps 2-7.



4.3 TEST DATA OF CONDUCTED EMISSION

EUT: CPU BOARD

MODEL: PCA-6168 SERIES

6 dB Band Width: 10 kHz

PHASE: LINE (L)

Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
[MHz]	Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.160	0.1	39.6	-	39.7	-	79.0	66.0	-39.3	-
0.184	0.2	44.6	-	44.8	-	79.0	66.0	-34.2	-
0.549	0.2	30.7	-	30.9	-	73.0	60.0	-42.1	-
3.430	0.2	46.9	-	47.1	-	73.0	60.0	-25.9	-
9.072	0.6	39.6	-	40.2	-	73.0	60.0	-32.8	-
19.540	1.2	32.5	-	33.7	-	73.0	60.0	-39.3	-

- Remarks:
1. "*": Undetectable
 2. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 3. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 4. The emission levels of other frequencies were very low against the limit.
 5. Margin value = Emission level - Limit value
 6. Emission Level = Correction Factor + Reading Value.



TEST DATA OF CONDUCTED EMISSION

EUT: CPU BOARD

MODEL: PCA-6168 SERIES

6 dB Band Width: 10 kHz

PHASE: NEUTRAL (N)

Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
[MHz]	Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.160	0.1	33.7	-	33.8	-	79.0	66.0	-45.2	-
0.184	0.2	46.5	-	46.7	-	79.0	66.0	-32.3	-
0.549	0.2	31.9	-	32.1	-	73.0	60.0	-40.9	-
3.430	0.2	45.7	-	45.9	-	73.0	60.0	-27.1	-
9.072	0.6	39.1	-	39.7	-	73.0	60.0	-33.3	-
19.540	1.1	35.4	-	36.5	-	73.0	60.0	-36.5	-

- Remarks:
1. "*": Undetectable
 2. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 3. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 4. The emission levels of other frequencies were very low against the limit.
 5. Margin value = Emission level - Limit value
 6. Emission Level = Correction Factor + Reading Value.



4.4 TEST DATA OF RADIATED EMISSION

EUT: **CPU BOARD**

MODEL: **PCA-6168 SERIES**

ANT. POLARITY: Horizontal

DETECTOR FUNCTION: Quasi-peak

6 dB BANDWIDTH: 120 kHz

FREQUENCY RANGE: 30-1000 MHz

MEASURED DISTANCE: 10 M

Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)
130.89	14.0	20.5	34.5	40.0	-5.5	400	7
170.12	11.4	22.1	33.5	40.0	-6.5	400	357
216.03	13.0	20.9	33.9	40.0	-6.1	400	195
261.88	16.7	15.7	32.4	47.0	-14.6	400	193
434.36	20.2	22.8	43.0	47.0	-4.0	215	315
958.05	28.2	2.8	31.0	47.0	-16.0	198	300

- REMARKS:
1. Emission level (dBuV/m) = Correction Factor (dB)
+ Reading value (dBuV).
 2. Correction Factor (dB) = Ant. Factor (dB)+Cable loss (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level - Limit value



TEST DATA OF RADIATED EMISSION

EUT: **CPU BOARD**

MODEL: **PCA-6168 SERIES**

ANT. POLARITY: Vertical

DETECTOR FUNCTION: Quasi-peak

6 dB BANDWIDTH: 120 kHz

FREQUENCY RANGE: 30-1000 MHz

MEASURED DISTANCE: 10 M

Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)
170.13	11.5	23.8	35.3	40.0	-4.7	100	8
176.68	11.4	15.4	26.8	40.0	-13.2	100	180
209.40	13.1	17.1	30.2	40.0	-9.8	100	171
222.47	13.7	18.7	32.4	40.0	-7.6	100	325
248.65	14.9	15.2	30.1	47.0	-16.9	100	102
268.29	15.8	17.7	33.5	47.0	-13.5	100	213
606.81	24.2	17.0	41.2	47.0	-5.8	220	269

- REMARKS:
1. Emission level (dBuV/m) = Correction Factor (dB)
+ Reading value (dBuV).
 2. Correction Factor (dB) = Ant. Factor (dB)+Cable loss (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level - Limit value



5. TEST RESULTS (IMMUNITY)

5.1 GENERAL DESCRIPTION

Generic Standard	:	EN 50082-2: 1995
Basic Standard	:	EN 61000-4-2 (Electrostatic Discharge, ESD, 8kV air discharge, 4kV Contact discharge, Performance Criterion B)
Specification and Performance Criteria	:	EN 61000-4-3 (Radio-Frequency Electromagnetic Field Susceptibility Test, RS, 80-1000 MHz, 10V/m, 80% AM (1kHz), Performance Criterion A)
	:	EN 61000-4-4 (Electrical Fast Transient/Burst, EFT, Power line: 2kV, Signal line: 1kV, Performance Criterion B)
	:	EN 61000-4-6 (Conducted Radio Frequency Disturbances Test, CS, 0.15-80 MHz, 10V/m, 80% AM, 1kHz, Performance Criterion A)
	:	EN 61000-4-8 (Power Frequency Magnetic Field Test, 50 Hz, 30A/m, Performance Criterion A)
	:	ENV 50204 (Radio-Frequency Electromagnetic Field, Pulse modulated, 900+/-5 MHz, 10V/m, 50 % duty cycle, Rep. Frequency 200 Hz, Performance Criterion A)
Input Voltage	:	230 Vac, 50 Hz
Temperature	:	21 degree C
Humidity	:	53 %
Atmospheric Pressure	:	1000 mbar

5.2 PERFORMANCE CRITERIA DESCRIPTION

- Criterion A - The apparatus shall continue to operate as intended. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended.
- Criterion B - The apparatus shall continue to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended.
- Criterion C - Temporary loss of function is allowed, provided the function is self-recoverable or can be restored by the operation of the controls.

5.3 EUT OPERATION CONDITION

The industrial PC runs a test program to receive picture messages from CCD cameras, which then send picture messages to monitor screen.



5.5 TEST RESULT OF RADIATED ELECTROMAGNETIC FIELDS (RS)

Basic Standard : EN 61000-4-3
Frequency range : 80 MHz - 1000 MHz
Field strength : 10 V/m
Modulation : 1kHz Sine Wave, 80% AM Modulation
Frequency step : 1 % of fundamental
Polarity of Antenna : Horizontal and Vertical
Test distance : 3 m

Test Result		Remarks
Criterion A	PASS	Model: PCA-6168 SERIES

Note: Four sides of EUT are verified separately.

Description of test result:

There was no change compared with initial operation during the test.



5.6 TEST RESULT OF ELECTRICAL FAST TRANSIENT (EFT)

Basic Standard : EN 61000-4-4
Test Voltage : Power Line - 2 kV
Signal/Control Line - 1 kV
Polarity : Positive/Negative
Impulse Frequency : 5 kHz
Tr / Tn : 5/50 ns
Burst Duration : 15 ms
Burst Period : 300 ms
Test Duration : Not less than 1 min.

Test Result		Remarks
Criterion A	PASS	Model: PCA-6168 SERIES

OBSERVATION DESCRIPTION

Test Point	Polarity	Test Level (kV)	Result
L1	+ / -	2	Note 1
L2	+ / -	2	Note 1
GND	+ / -	2	Note 1
Signal/Control Line	+ / -	1	Note 1

Description of test result:

Note 1: There was no change compared with initial operation during the test.



5.7 TEST RESULT OF CONDUCTED RADIO FREQUENCY

DISTURBANCES (CS)

Basic Standard : EN 61000-4-6
Frequency range : 0.15 MHz - 80 MHz
Field strength : 10 V/m
Modulation : 1kHz Sine Wave, 80%, AM Modulation
Frequency step : 1 % of fundamental
Coupled cable : Power Mains, Unshielded
Coupling device : CDN-M3 (3 wires)

Test Result		Remarks
Criterion A	PASS	Model: PCA-6168 SERIES

OBSERVATION DESCRIPTION

There was no change compared with initial operation during the test.



5.8 TEST RESULT OF POWER FREQUENCY MAGNETIC FIELD

Basic Standard : EN 61000-4-8
Frequency range : 50Hz
Field strength : 30 A/m
Observation Time : 1 minute
Inductance coil : Rectangular type, 1mx1m

Test Result		Remarks
Criterion A	PASS	Model: PCA-6168 SERIES

OBSERVATION DESCRIPTION

There was no change compared with initial operation during the test.



5.9 TEST RESULT OF RADIO-FREQUENCY ELECTROMAGNETIC FIELD, PULSE MODULATED

Basic Standard : ENV 50204
Frequency range : 900 +/- 5 MHz
Field strength : 10 V/m
Modulation : 200Hz, Square Wave, 50% Duty Cycle
Dwell Time : 30 second
Polarity of Antenna : Horizontal and Vertical
Test distance : 3 m

Test Result		Remarks
Criterion A	PASS	Model: PCA-6168 SERIES

Note: Four sides of EUT are verified separately.

OBSERVATION DESCRIPTION


There was no change compared with initial operation during the test.

6. PHOTOGRAPHS OF THE TEST CONFIGURATION

CONDUCTED EMISSION TEST



RADIATED EMISSION TEST



ESD TEST



1


3

2



4

RS TEST & PULSE MODULATION TEST



EFT TEST



EFT CLAMP TEST




CONDUCTED SUSCEPTIBILITY TEST



CS CLAMP TEST



MAGNETIC TEST





7. APPENDIX - INFORMATION OF THE TESTING LABORATORY

Information of the testing laboratory

We, ADT Corp., are founded in 1988, to provide our best service in EMC and Safety consultation. Our laboratory is accredited by the following approval agencies according to ISO/IEC Guide 25 or EN 45001:

- | | |
|---------------|--------------------------------------|
| ● USA | FCC, UL, NVLAP |
| ● Germany | TUV Rheinland
TUV Product Service |
| ● Japan | VCCI |
| ● New Zealand | RFS |
| ● Norway | NEMKO, DNV |
| ● U.K. | INCHCAPE, SGS |
| ● R.O.C. | BSMI |

Enclosed please find some certificates of our laboratory obtained from approval agencies. If you have any comments, please feel free to contact us with the following:

Lin Kou EMC Lab.:
Tel: 886-2-26032180
Fax: 886-2-26022943

Hsin Chu EMC Lab:
Tel: 886-35-935343
Fax: 886-35-935342

Lin Kou Safety Lab.:
Tel: 886-2-26093195
Fax: 886-2-26093184

Design Center:
Tel: 886-2-26093195
Fax: 886-2-26093184

E-mail: service@mail.adt.com.tw
<http://www.adt.com.tw>