

# IPPC-6152F

15" XGA TFT LCD Celeron® M Fanless Industrial Panel PC with 2 x PCI Slots



## Features

- 15" XGA TFT LCD with touchscreen (optional)
- Intel® Celeron® M ULV 1GHz processor on board
- 1GB DDR2 SDRAM system memory
- Fanless cooling system
- 24VDC power supply
- Offers two expansion slots for PCI add-on cards
- Dual Lan, supports one Gigabit Lan
- Front USB access and system reset function
- Flat-sealed front panel
- Control box with gull-wing design for easy installation and maintenance
- Front panel is NEMA4/IP65 compliant
- Heavy-duty aluminum front panel

## Introduction

The IPPC-6152F is an Industrial Panel PC with front USB access, supports Celeron M ULV 1GHz, 1GB DDR2 memory, one CompactFlash slot and two PCI expansion slots. The flat-sealed front panel design for easier cleaning and liquid run off. Also the control box has the gull-wing design for easy components installation and maintenance. The design of fanless cooling system and spindle-free storage makes IPPC-6152F a durable and reliable platform. A fast-access SATA HDD is option. Two PCI slots meets diverse requests.

## Specifications

### General

- **BIOS** Award® 256 KB Flash BIOS
- **Certifications** UL, CE, FCC, CCC, BSMI
- **Cooling System** Fanless design
- **Dimension (W x H x D)** 449.92 x 315.63 x 141.7 (17.73" x 12.44" x 5.58")
- **Mounting** Panel, Rack (option)
- **Power Input** 10 ~ 30VDC, 18A
- **Power Output** +3.3V@8A, +5V@10A, +12V@4A, +5Vsb@0.75A, -12V@1A
- **Power Supply** 85W
- **Weight (Gross)** 10 Kg

### System Hardware

- **Audio Ports** Mic-in, Line-in, Line-out
- **Chipset** Intel 915 GME
- **CPU** Intel Celeron M ULV 1GHz on board
- **Memory** 1GB DDR2 SDRAM 400/533MHz
- **Storage** 1 x CompactFlash Slot  
1 x 2.5" SATA HDD (optional)
- **Network (LAN)** 10/100Base-T Ethernet x 1  
Gigabit Ethernet x 1
- **Bus Expansion** 2 x low-profile PCI slots (total 25W)
- **Keyboard/Mouse** PS/2 interface
- **Parallel Port** 1 x enhanced parallel port, supports SPP/EPP/ECP parallel model. BIOS configurable to LPT1, LPT2, LPT or disabled
- **Serial Port** 1 x RS-232
- **USB Ports** 4 x USB 2.0 + 1 x USB2.0 @ front panel
- **Video Port** VGA

### LCD Display

- **Backlight Life** 50,000 hrs
- **Contrast Ratio** 500 : 1
- **Display Size** 15"
- **Display Type** XGA TFT LCD
- **Luminance** 250 cd/m<sup>2</sup>
- **Max. Colors** 16.2 M  
(RGB 6-bit + FRC data)
- **Max. Resolution** 1024 x 768
- **Viewing Angle (H/V°)** 140/120

### Touchscreen (Optional)

- **Interface** RS-232
- **Lifespan** 10 millions times touch at single point
- **Light Transmission** > 80%
- **OS Support** Windows® 95/98/ME/2000/XP/CE/NT/Vista, Linux, MS-DOS
- **Type** Analog resistive 8-wire

### Environment


- **Humidity** 5 ~ 85% @ 40 °C (non-condensing)
- **Ingress Protection** Front panel: NEMA 4/IP 65
- **Operating Temperature** 0 ~ 50 °C (32 ~ 122 °F)
- **Storage Temperature** -20 ~ 60 °C (-4 ~ 140°F)
- **Vibration Protection** 5 ~ 500 Hz, 1 Grms random vibration

## Ordering Information

- **IPPC-6152F-X0AE** 15" XGA TFT LCD Celeron M Fanless Industrial Panel PC with 2 x PCI Slots
- **IPPC-6152F-R0AE** 15" XGA TFT LCD Celeron M Fanless Industrial Panel PC with 2 x PCI Slots and Resistive Touchscreen

**Dimensions**


Unit: mm



**Accessories**

- IPPC-6152A-RMKE IPPC-6152A/FPM-5151G Rack Mount Kit
- 1702002600 Power Cable US Plug 1.8 M
- 1702002605 Power Cable EU Plug 1.8 M
- 1702031801 Power Cable UK Plug 1.8 M
- 1702031836 Power Cable China/Australia Plug 1.8 M

**I/O View**



**Front Accessible USB Port**

