

PCM-3813I

PCM-3718H/HG/HO


PCM-3724

100 kS/s, 12-bit, 32-ch, Isolated Analog Input PCI-104 Module


100 kS/s, 12-bit, 16-ch PC/104 Multifunction Module

48-ch Digital I/O PC/104 Module


NEW



PCM-3813I



PCM-3718H/HG/HO



PCM-3724



Features

- 32 single-ended or 16 differential analog inputs
- 12-bit A/D converter, with up to 100 kHz sampling rate
- Programmable gain for each input channel
- Automatic channel/ gain/ SD scanning
- Onboard ring buffer (1,024 samples)
- Isolation protection (2,500 V_{DC})
- Software polling, internal or external pacer sampling modes supported
- BoardID™ switch

Specifications

Analog Input

- Channels** 32 single-ended or 16 differential or combination
- Resolution** 12 bits
- Max. Sampling Rate** 100 kS/s
- Ring Buffer Size** 1k samples
- Input Range and PGA Bandwidth**

Gain	0.5	1	2	4	8
Unipolar	N/A	0 ~ 10	0 ~ 5	0 ~ 2.5	0 ~ 1.25
Bipolar	±10	±5	±2.5	±1.25	±0.625
Bandwidth	5.0 MHz	5.0 MHz	4.0 MHz	1.3 MHz	0.6 MHz

- Input Protect** 30 Vp-p
- Input Impedance** 100 MW/10pF (Off); 100 MW/100pF (On)
- Trigger Mode** Software polling, onboard programmable pacer, or external TTL trigger

General

- Bus Type** PCI-104
- I/O Connectors** 1 x IDC-40 pin
- Dimensions (L x H)** 96 x 90 mm (3.8" x 3.5")
- Operating Temperature** 0 ~ 60° C (32 ~ 140° F) (refer to IEC 68-2-1,2)
- Storage Temperature** -20 ~ 70° C (-4 ~ 158° F)

Ordering Information

- PCM-3813I** 100 kS/s, 12-bit, 32-ch, Isolated Analog Input PCI-104 Module
- ADAM-3937** DB37 Wiring Terminal for DIN-rail Mounting

Specifications

Analog Input

- Channels** 16 single-ended, or 8 differential inputs
- Resolution** 12 bits
- Max. Sampling Rate** 100 KHz* (DMA transfer) *80 kHz on P4-based (or upper) system
- Input Impedance** 10 MW
- Sampling Modes** Software, pacer or ext.

Input Range

- 80 kHz on P4-based (or upper) system

PCM-3718H and PCM-3718HO	Bipolar	±10, ±5, ±2.5, ±1.25, ±0.625
	Unipolar	0 ~ 10, 0 ~ 5, 0 ~ 2.5, 0 ~ 1.25
PCM-3718HG	Bipolar	±10, ±5, ±1, ±0.5, ±0.1, ±0.05, ±0.01, ±0.005
	Unipolar	0 ~ 10, 0 ~ 1, 0 ~ 0.1, 0 ~ 0.01

Analog Output (PCM-3718HO only)

- Channels** 1 (12 bits)
- Output Rate** Static update
- Output Range**

Internal Reference	Unipolar (V)	0 ~ 5, 0 ~ 10
External Reference (V)		0 ~ 10, 0 ~ -10

- Slew Rate** 10 V/μs
- Driving Capability** 10 mA
- Output Impedance** 0.1 Wmax.
- Accuracy** Relative: ±1 LSB

Digital Input/Output

- Channels** 16, 5V/TTL
- Input Voltage** Logic 0: 0.8 V max. Logic 1: 2.0 V min.
- Output Voltage** Logic 0: 0.33 V max. @ 6 mA (sink) Logic 1: 3.84 V min. @ 6 mA (source)

General

- Bus Type** PC/104
- I/O Connectors** 2 x 20-pin box header
- Dimensions (L x H)** 96 x 90 mm (3.8" x 3.5")
- Power Consumption** Typical: 5 V @ 180 mA Max.: 5 V @ 400 mA
- Operating Temperature** 0 ~ 60° C (32 ~ 140° F)
- Storage Temperature** -40 ~ 85° C (-40 ~ 185° F)

Ordering Information

- PCM-3718H** 12-bit Multifunction Module w/Programmable Gain (cable not included)
- PCM-3718HG** PCM-3718H w/high gain
- PCM-3718HO** PCM-3718H w/AO
- ADAM-3920** 20-pin flat cable wiring terminal for DIN-rail
- PCLD-780** Screw-terminal board for 20-pin flat cable
- PCL-10120-1** 20-pin flat cable, 1 m
- PCL-10120-2** 20-pin flat cable, 2 m

Features

- 48 TTL digital I/O lines
- Supports dry contact and wet contact
- Keeps the I/O port setting and DO state after system reset
- Output status read-back
- Channels simulate 8255 PPI mode 0
- Interrupt triggering, rising/falling edge

Specifications

Digital Input

- Channels** 48 (shared with output)
- Compatibility** 5 V/TTL
- Input Voltage** Logic 0: 0.8 V max. Logic 1: 2.0 V min.
- Interrupt Capable Ch.** 1

Digital Output

- Channels** 48 (shared with input)
- Compatibility** 5 V/TTL
- Output Voltage** Logic 0: 0.5 V max. @ 6 mA (sink) Logic 1: 2.0 V min. @ -6 mA (source)

General

- Bus Type** PC/104
- I/O Connectors** 2 x 50-pin box header
- Dimensions (L x H)** 96 x 90 mm (3.8" x 3.5")
- Power Consumption** 5 V @ 90 mA
- Operating Temperature** 0 ~ 60° C (32 ~ 140° F)
- Storage Temperature** -40 ~ 85° C (-40 ~ 185° F)

Ordering Information

- PCM-3724** 48-ch DI/O Module (cable not included)
- ADAM-3950** 50-pin flat cable wiring terminal for DIN-rail mounting
- PCLD-785B** 24-ch Relay Output Board
- PCLD-782B** 24-ch Opto-isolated DI Board
- PCL-10150-1.2** 50-pin flat cable, 1.2 m