


# PCM-4862

486 SBC with VGA/LCD, Ethernet and SSD



## Features

- 10Base-T Ethernet
- 24-bit LCD interface
- Versatile SSD
- Supports CT6545

## Specifications

- **CPU** Socket 7 for DX4-100 or DX5-133 CPU
- **System Memory** EDO/FPM SIMM x 2, Max. 64 MB
- **2nd Cache Memory** On board 128 KB
- **System Chipset** VIA VT82C496G//82C416
- **BIOS** AWARD 128 KB Flash BIOS
- **SSD** Supports DiskOnChip
- **Watchdog Timer** 1 - 62 sec. 62 level timer intervals, system reset or IRQ11
- **Expansion Interface** PC/104
- **Battery** Lithium 3 V/196 mAH

### I/O

- **MIO** 1 x EIDE, 1 x FDD, 1 x K/B, 1 x Mouse, 1 x RS-232/422/485, 1 x RS-232, 1 x LPT

### Ethernet

- **Chipset** RealTek RTL8019A
- **Interface** IEEE 802.3i 10Base-T Ethernet compatible  
Built-in boot ROM in Flash BIOS

### Display

- **Chipset** Asiliant (C&T) 65545
- **Memory Size** 512 KB (optional 1 MB)
- **Resolution** Up to 1024 x 768 @ 16 colors non-interlaced CRT and 640 x 480 @ 256 colors LCD (512 KB VRAM)
- **LCD Interface** Up to 24-bit TTL for STN/DSTN/TFT LCD



## Mechanical and Environmental

- **Dimensions (L x W)** 203 x 146 mm (8" x 5.75")
- **Power supply Voltage** +5 V  $\pm$  5%  
Max. : 4 A @ +5 V  
Typical: 2 A @ +5 V (with 32 MB DRAM, AMD DX5-133)
- **Operating temperature** 0 ~ 60°C (32~140° F)
- **Operating Humidity** 0% ~ 90% Relative Humidity, noncondensing
- **Weight** 0.3 kg (weight of total package)

## Packing List

- 1 PCM-4862 SBC
- 1 Mini Jumper pack (count.: 10 pcs) (p/n: 9689000002)
- Startup manual
- Utility CD

## Ordering Information

### Standard

- **PCM-4862-00A3** 486 SBC with VGA/LCD, Ethernet and SSD
- **PCM-4862-01A3** same as PCM-4862-00A3, but with 1 MB VGA

### Optional

- **PCM-10586-1000** PCM-4862 wiring kit
- **MBPC-300-4862** MicroBox 5.25" Biscuit SBC chassis for PCM-4862
- **PS-55A** 55 W AC power supply for MBPC-300
- **1961000100** Heatsink only for 486 CPU
- **1759202300** 486 CPU fan with heatsink