SG-1003/1103

SOHO Security Gateway with 3 LAN



Features

- · Compact fanless Firewall/VPN platform for SOHO
- 3 10/100 Mbps Ethernet ports for LAN, WAN, and DMZ
- Supports COM, VGA and PS2 port for local system management

Introduction

A compact fanless Security Gateway, the SG-1103 is specifically designed for Internet secure connectivity and is suitable for the SOHO Firewall/VPN. Designed with the SiS550 200 MHz processor, it has low power consumption that can meet the requirements needed for SOHO Firewall/VPN appliances. The system supports a CompactFlash used for installing OS and Firewall/VPN applications, which totally avoids the service disruption caused by hard disk mechanical/magnetic failures. In addition, the SG-1103 can support system memory up to 512 MB SDRAM. The SG-1103 offers three 10/100 Mbps auto-sensing Fast Ethernet ports for WAN, LAN, and DMZ connections. Also offers COM, VGA and PS2 ports for local system management, maintenance, and diagnostics.

Specifications:

- · CPU & Chipset: SiS550 200 MHz
- BIOS: AWARD 256 KB Flash memory
- System Memory: One 144-pin SODIMM socket accepts up to 512 MB SDRAM (Default 128MB included)
- · Storage: one CompactFlash Type I/II
- I/O: 1 x RS-232 port, 3 x RJ-45 LAN port, VGA (SG-1103), and PS/2 keyboard & mouse (SG-1103)
- Ethernet Chipset: RealTek 8139CL
- Operating temperature: 0 ~ 40°C (32 ~ 104°F)
- · Power supply: AC/DC power adapter, DC 5V input
- Storage temperature: -20 \sim 75°C (-4 \sim 167°F)
- Operating humidity: 5 ~ 95% @ 40°C, non-condensing
- Storage humidity: $5 \sim 95\%$
- **Dimensions**: 228 mm x 44 mm x 146 mm (W x H x D)
- · EMI/EMC: FCC Class A

Ordering Information

- □ SG-1003: SOHO Security Gateway with 3 LAN
- □ SG-1103: SOHO Security Gateway with 3 LAN/VGA/PS2



Note: All specifications are subject to change without notice.