

# ADAM-5510EKW/TP

8-slot Ethernet-enabled SoftLogic Controller



RoHS COMPLIANT 2005/618/EC CE FCC

## Features

- 10/100Base-T Ethernet interface
- Built-in Modbus/TCP server
- Supports Modbus/TCP client
- Supports Modbus/RTU Master
- Supports Modbus/RTU Slave
- Supports Multiprog via Ethernet
- IEC-61131-3 standard package
- Supports LD/FB/SFC/IL/ST Languages
- Cross-Language compiling program
- 8 I/O slots base and handles up to 128 Local I/O Points
- Supports AI/AO/DI/DO/Counter Function Blocks

## Introduction

The ADAM-5510EKW/TP is an Ethernet-enabled SoftLogic Controller. In addition to the features of ADAM-5510KW and ADAM-5510EKW, the ADAM-5510EKW/TP has Ethernet features including Modbus/TCP Server, Modbus/TCP Client and Multiprog via Ethernet functions. Therefore, users can easily and quickly complete their programming based on Ethernet architecture.

### Standard Modbus Interface

For advanced system integration, the ADAM-5510EKW/TP supports not only Modbus/RTU Master and Slave functions via serial ports, but also the Modbus/TCP Client to retrieve data from remote I/O, and Modbus/TCP Server to send data back to the HMI/SCADA Software via Ethernet port. Furthermore, the ADAM-5510EKW/TP allows users to remotely maintain multiple ADAM-5510EKW/TP controllers by running Multiprog programming software via Ethernet.

## Specifications

### Control System

- **CPU** 16-bit microprocessor
- **I/O Capacity** 8 slots
- **LED Indicators** Power, CPU, communication, and battery
- **Memory** Flash disk: 512 KB  
Flash memory: 768 KB  
Flash ROM: 256 KB  
RAM: 640 KB SRAM, 17 KB with battery backup
- **Operating System** ROM-DOS
- **Real-time Clock** Yes
- **Watchdog Timer** Yes

### Communications (Ethernet)

- **Medium** Cat.5 cable with RJ-45 connectors
- **Transmission Speed** 100 Mbps (10/100Base-T)

### Communications (Serial)

- **Max. Nodes** 32 (in RS-485 daisy-chain network)
- **Medium** RS-485 (2-wire)
- **Protocols** Modbus/RTU, Modbus/TCP
- **Transmission Speed** 9600, 19200 and 38400 bps

### Protection

- **Power Input** 3000 V<sub>DC</sub>
- **Communication Line Isolation** 2500 V<sub>DC</sub> (COM2 only)
- **Power Reversal Protection** Yes

### Power

- **Power Consumption** 4 W @ 24 V<sub>DC</sub> (not including I/O modules)  
Unregulated 10 ~ 30 V
- **Power Input** Unregulated 10 ~ 30 V<sub>DC</sub>

### General

- **Certifications** CE, FCC class A
- **Connectors** 1 x DB9-M for RS-232/485 (COM1)  
1 x Screw terminal for RS-485 (COM2)  
1 x DB9-F for RS-232/Programming (COM3)  
1 x DB9-M for RS-232/485 (COM4)  
1 x Screw-terminal for power input  
1 x RJ-45 for LAN
- **Dimensions** 355 x 110 x 75 mm
- **Enclosure** ABS+PC
- **Mounting** DIN 35 rail, stack, wall

### Environment

- **Humidity** 5 ~ 95%, non-condensing
- **Operating Temperature** -10 ~ 70 °C (14 ~ 158 °F)
- **Storage Temperature** -25 ~ 85 °C (-13 ~ 185 °F)

## Ordering Information

- **ADAM-5510EKW/TP** 8-slot Ethernet-enabled SoftLogic Controller
- **MProg-BAS33** KW Multiprog SoftLogic Development Kit Basic Edition v3.3 for Windows® NT/2000/XP (128-byte I/O)

1  
PAC & Software

2  
BAS

3  
UNO

4  
RS-485 I/O

5  
Ethernet I/O

6  
TPC

7  
IPPC

8  
FPM

9  
AWS

10  
Plug-in I/O

11  
CompactPCI

12  
Signal Conditioning

13  
USB I/O

14  
Motion Control I/O

15  
Ethernet Switch

16  
EDG

17  
ICOM