

USB-4622

5-port USB 2.0 Hub



Features

- 5 downstream USB 2.0 ports
- Compatible with USB 2.0/1.1/1.0
- 480Mbps high-speed data transfer
- LED indicator
- Suitable for DIN-rail mounting
- Lockable USB cable
- 10~30VDC power input (power adapter not included)

Introduction

USB-4622 is a USB 2.0 hub capable of connecting at most 5 USB slave modules. It supports the USB 2.0 high-speed mode that can achieve 480Mbps data transmitting rate, realizing the USB-4700 series' high performance for heavy-loaded applications. The Advantech's unique lockable cable design secures the slave module connections, preventing the cable from being unplugged accidentally.

Specifications

- **Ports:** Upstream x 1 (TypeB)
Downstream x 5 (TypeA)
- **Compatibility:** Universal Serial Bus
Specification Rev. 2.0/1.1/1.0
- **Transfer Speed:** 480 Mbit/s-High Speed Mode
12 Mbit/s- Full Speed Mode
1.5 Mbit/s-Low Speed Mode
- **Supply Current:** 500 mA max. per channel

General

- **Housing:** Plastic (ABS+PC)
- **Dimensions:** 132 x 80 x 32 mm
- **DC Input:** 10~30VDC
- **Power Consumption:** +24V@36mA
- **Operating Temperature:** 0~60° C (32~140° F)
- **Storage Temperature:** -20~70° C (-4~158° F)
- **Storage Humidity:** 5~95% RH non-condensing

Ordering Information

- **USB-4622** 5-port USB 2.0 Hub (Power adapter not included)

Accessories

- **PWR-243** Panel Mount Power Supply
- **PWR-244** Panel Mount Power Supply
- **1960004544** Wall Mount Bracket
- **1960005788** VESA Mount Bracket