



EMC COMPLIANCE TEST REPORT

for

Panel PC

Trade Name : ADVANTECH
Model Number : PPC-174T
Serial Number : N/A
Report Number : B30619003-E
Date : June 25, 2003
Regulations : See below

Standards	Results (Pass/Fail)
EN 55022: 1998 + A1: 2000	PASS
EN 61000-3-2: 1995 + A1: 1998 + A2: 1998	PASS
EN 61000-3-3: 1995	PASS
EN 55024: 1998	PASS
- IEC 61000-4-2: 2001	PASS
- IEC 61000-4-3: 1995	PASS
- IEC 61000-4-4: 1995	PASS
- IEC 61000-4-5: 1995	PASS
- IEC 61000-4-6: 1996	PASS
- IEC 61000-4-8: 1993	PASS
- IEC 61000-4-11: 1994	PASS

Prepared for:

Advantech Co., Ltd.
No. 1, Alley 20, Lane 26, Rueiguang Road, Neihu District,
Taipei 114, Taiwan, R.O.C.

Prepared by:



C&C LABORATORY, CO., LTD.
No. 81-1, 210 Lane, Pa-de 2nd Road, Lu-Chu Hsiang,
Taoyuan, Taiwan, R.O.C.
TEL: (03) 324-0332
FAX: (03) 324-5235



This report shall not be reproduced, except in full, without the written approval of
C&C LABORATORY, CO., LTD.

The client to claim product certification, approval or endorsement by NVLAP, NIST or any agency
of the federal government must not use this report.

TABLE OF CONTENTS

1	VERIFICATION OF COMPLIANCE	3
2	GENERAL INFORMATION	4
3	SYSTEM DESCRIPTION	5
4	PRODUCT INFORMATION	6
5	SUPPORT EQUIPMENT	7
6	TEST FACILITY	8
7	TEST EQUIPMENT LIST (EMISSION)	9
8	TEST EQUIPMENT LIST (IMMUNITY)	10
9	SECTION 1 EN 55022 (LINE CONDUCTED & RADIATED EMISSION)	11
9.1	MEASUREMENT PROCEDURE (PRELIMINARY LINE CONDUCTED EMISSION TEST)	11
9.2	MEASUREMENT PROCEDURE (COMMON MODE CONDUCTED EMISSION MEASUREMENT)	13
9.3	MEASUREMENT PROCEDURE (PRELIMINARY RADIATED EMISSION TEST)	14
10	BLOCK DIAGRAM OF TEST SETUP	16
11	SUMMARY DATA	17
12	SECTION 2 EN 61000-3-2 & EN 61000-3-3 (POWER HARMONICS & VOLTAGE FLUCTUATION / FLICKER)	21
13	SECTION 3 IEC 61000-4-2 (ELECTROSTATIC DISCHARGE)	29
14	SECTION 4 IEC 61000-4-3 (RADIATED ELECTROMAGNETIC FIELD)	34
15	SECTION 5 IEC 61000-4-4 (FAST TRANSIENTS/BURST)	37
16	SECTION 6 IEC 61000-4-5 (SURGE IMMUNITY)	39
17	SECTION 7 IEC 61000-4-6 (CONDUCTED DISTURBANCE/INDUCED RADIO-FREQUENCY FIELD)	41
18	SECTION 8 IEC 61000-4-8 (POWER FREQUENCY MAGNETIC FIELD IMMUNITY TEST)	43
19	SECTION 9 IEC 61000-4-11 (VOLTAGE DIPS, SHORT INTERRUPTIONS AND VOLTAGE VARIATIONS)	45
20	APPENDIX 1 PHOTOGRAPHS OF TEST SETUP	47
20.1	LINE CONDUCTED EMISSION TEST (EN 55022)	48
20.2	COMMON MODE CONDUCTED EMISSION TEST	49
20.3	RADIATED EMISSION TEST (EN 55022)	50
20.4	POWER HARMONIC & VOLTAGE FLUCTUATION / FLICKER TEST (EN 61000-3-2, EN 61000-3-3)	51
20.5	ELECTROSTATIC DISCHARGE TEST (IEC 61000-4-2)	52
20.6	RADIATED ELECTROMAGNETIC FIELD (IEC 61000-4-3)	53
20.7	FAST TRANSIENTS/BURST TEST (IEC 61000-4-4)	54
20.8	SURGE IMMUNITY TEST (IEC 61000-4-5)	55
20.9	CONDUCTED DISTURBANCE, INDUCED BY RADIO-FREQUENCY FIELDS TEST (IEC 61000-4-6)	56
20.10	POWER FREQUENCY MAGNETIC FIELD IMMUNITY TEST	57
20.11	VOLTAGE DIPS / INTERRUPTION TEST (IEC 61000-4-11)	58
21	APPENDIX 2 PHOTOGRAPHS OF EUT	59

1 VERIFICATION OF COMPLIANCE


Equipment Under Test: Panel PC
Trade Name: ADVANTECH
Model Number: PPC-174T
Serial Number: N/A
Applicant: **Advantech Co., Ltd.**
No. 1, Alley 20, Lane 26, Rueiguang Road, Neihu District,
Taipei 114, Taiwan, R.O.C.
Manufacturer: **Advantech Co., Ltd.**
No. 1, Alley 20, Lane 26, Rueiguang Road, Neihu District,
Taipei 114, Taiwan, R.O.C.
Type of Test: EMC Directive 89/336/EEC for CE Marking
Technical Standards: EN 55022: 1998 + A1: 2000
EN 61000-3-2: 1995 + A1: 1998 + A2: 1998
EN 61000-3-3: 1995
EN 55024: 1998 (IEC 61000-4-2: 2001, IEC 61000-4-3: 1995,
IEC 61000-4-4: 1995, IEC 61000-4-5: 1995,
IEC 61000-4-6: 1996, IEC 61000-4-8: 1993,
IEC 61000-4-11: 1994)
File Number: B30619003-E
Date of Test: June 19 ~ 20, 2003
Deviation: None
Condition of Test Sample: Normal
Final Result: Pass
Worst Data: See below

Test Item	Freq. (MHz)	Measured Data	Margin (M μ C)	Remark
Radiated Emission	202.00	26.2 (dB/m)	-3.8 dB (\pm 1.6672 dB)	
Conducted Emission	4.092	40.50 (dB)	-15.50 dB (\pm 2.8216 dB)	
<ul style="list-style-type: none">● The negative sign in Margin cell means under the specific limit.● This test result traceable to national or international standards.				

The above equipment was tested by C&C Laboratory Co., Ltd. for compliance with the requirements set forth in EMC Directive 89/336/EEC and the Technical Standards mentioned above. This said equipment in the configuration described in this report shows the maximum emission levels emanating from equipment and the level of the immunity endurance of the equipment are within the compliance requirements.

The test results of this report relate only to the tested sample identified in this report.

Approved by:



Jonson Lee / EMC Director

Reviewed by:



Jessie Wang / Section Manager

2 GENERAL INFORMATION

Applicant: Advantech Co., Ltd.
No. 1, Alley 20, Lane 26, Rueiguang Road, Neihu District,
Taipei 114, Taiwan, R.O.C.

Contact Person: John Chou

Manufacturer: Advantech Co., Ltd.
No. 1, Alley 20, Lane 26, Rueiguang Road, Neihu District,
Taipei 114, Taiwan, R.O.C.

File Number: B30619003-E

Date of Test: June 19 ~ 20, 2003

Equipment Under Test: Panel PC

Model Number: PPC-174T

Serial Number: N/A

Type of Test: EMC Directive 89/336/EEC for CE Marking

Technical Standards: EN 55022: 1998 + A1: 2000
EN 61000-3-2: 1995 + A1: 1998 + A2: 1998
EN 61000-3-3: 1995
EN 55024: 1998 (IEC 61000-4-2: 2001, IEC 61000-4-3: 1995,
IEC 61000-4-4: 1995, IEC 61000-4-5: 1995,
IEC 61000-4-6: 1996, IEC 61000-4-8: 1993,
IEC 61000-4-11: 1994)

**Frequency Range
(EN 55022):** 150kHz to 30MHz for Line Conducted Test
30MHz to 1000MHz for Radiated Emission Test

Test Site: C&C LABORATORY CO., LTD.
No. 81-1, 210 Lane, Pa-de 2nd Road, Lu-Chu Hsiang,
Taoyuan, Taiwan, R.O.C.

3 SYSTEM DESCRIPTION

EUT Test Program:

1. EMI test program was loaded and executed in Windows 2000 mode.
2. The EMI test program sequentially exercised all I/O's of EUT.
3. A communicated software was loaded and executed to communicate between EUT and remote side.
4. The EUT receives message from remote side, and filling the screen of monitor with upper case of "H" patterns.
5. Repeat 2 to 4. Test program is self-repeating throughout the test.

4 PRODUCT INFORMATION

Housing Type: Plastic w/ metal plate
EUT Power Rating: 100-240VAC, 60-50MHz, 4-2A
AC power during Test: 230VAC/ 50Hz
Power Supply Manufacturer: FSP **Model:** FSP180-50PLA
AC Power Cord Type: Unshielded, 1.8m (Detachable)
CPU Manufacturer: Intel **Model:** P4 2.4GHz
OSC/Clock Frequencies: 133MHz
Memory Capacity: **Installed:** 256MB
LCD Panel Manufacturer: AU **Model:** M170EN05
HDD Manufacturer: Maxtor **Model:** 6E040L0 (40GB)
FDD Manufacturer: NEC **Model:** FD3238T
CD-ROM Manufacturer: ASUS **Model:** SCD-2400

I/O Port of EUT

I/O PORT TYPES	Q'TY	TESTED WITH
1). Parallel Port	1	1
2). Serial Port	3	3
3). Video Out Port (VGA)	1	1
4). PS/2 Mouse Port	1	1
5). PS/2 Keyboard Port	1	1
6). Audio In Port	1	1
7). Audio Out Port	1	1
8). Microphone Port	1	1
9). LAN Port	1	1
10).USB Port	4	4
11).S-Video Out Port	1	1

5 SUPPORT EQUIPMENT

No.	Equipment	Model #	Serial #	FCC ID	Trade Name	Data Cable	Power Cord
1.	Monitor	959NF	AQ19H2RT706137Y	FCC DoC	SAMSUNG	Shielded, 1.8m with two cores	Unshielded, 1.8m
2.	Modem	DM-1414	0304012269	IFAXDM1414	ACEEX	Shielded, 1.8m	Unshielded, 1.8m
3.	Printer	STYLUS C60	DR3K041995	FCC DoC	EPSON	Shielded, 1.8m	Unshielded, 1.8m
4.	PS/2 Keyboard	KB-0133	N/A	FCC DoC	Compaq	Shielded, 1.8m	N/A
5.	PS/2 Mouse	M-S69	N/A	FCC DoC	Compaq	Shielded, 1.8m	N/A
6.	Mouse	M-MM43	LZE93353074	FCC DoC	Logitech	Shielded, 1.8m	N/A
7.	Mouse	M-MM43	LZE94052791	FCC DoC	Logitech	Shielded, 1.8m	N/A
8.	USB 2.0 External HDD	ME-911U2	N/A	FCC DoC	Portable	Shielded, 1.8m	N/A
9.	USB 2.0 External HDD	ME-911U2	N/A	FCC DoC	Portable	Shielded, 1.8m	N/A
10.	USB 2.0 External HDD	ME-911U2	N/A	FCC DoC	Portable	Shielded, 1.8m	N/A
11.	USB 2.0 External HDD	ME-911U2	N/A	FCC DoC	Portable	Shielded, 1.8m	N/A
12.	Walkman	RQ-L10	HB004471	FCC DoC	Panasonic	Unshielded, 1.8m	N/A
13.	Multimedia Earphone	Axis-301	N/A	FCC DoC	Labtec	Unshielded, 1.25m	N/A
14.	V8	CCD-TRV310	N/A	FCC DoC	SONY	S-Video Cable: Shielded, 1.8m	N/A
15.	Notebook PC (Remote)	M285	NU2503589	FCC DoC	LEO	LAN Cable: Unshielded, 10m	AC Cable: Unshielded, 1.8m DC Cable: Unshielded, 1.8m with a core

Note: All the above equipment/cables were placed in worse case positions to maximize emission signals during emission test.

Grounding: Grounding was in accordance with the manufacturer's requirements and conditions for the intended use.

6 TEST FACILITY

- Location:** No. 81-1, 210 Lane, Pa-de 2nd Road, Lu-Chu Hsiang, Taoyuan, Taiwan, R. O. C.
- Description:** There are four 3/10m open area test sites and three line conducted labs for final test. The Open Area Test Sites and the Line Conducted labs are constructed and calibrated to meet the FCC requirements in documents ANSI C63.4: 1992 and CISPR 16 requirements.
- Site Filing:** A site description is on file with the Federal Communications Commission, 7435 Oakland Mills Road, Columbia, MD 21046.
- Registration also was made with Voluntary Control Council for Interference (VCCI).
- Site Accreditation:** Accredited by NEMKO (Authorization #: ELA 124) for EMC & A2LA (Certificate #: 824.01) for Emission
- Accredited by NVLAP (Certificate #: 200600-0)
- Also accredited by BSMI for the product category of Information Technology Equipment.
- Instrument Tolerance:** All measuring equipment is in accord with ANSI C63.4 and CISPR 22 requirements that meet industry regulatory agency and accreditation agency requirement.
- Ground Plane:** Two conductive reference ground planes were used during the Line Conducted Emission, one in vertical and the other in horizontal. The dimensions of these ground planes are as below. The vertical ground plane was placed distancing 40 cm to the rear of the wooden test table on where the EUT and the support equipment were placed during test. The horizontal ground plane projected 50 cm beyond the footprint of the EUT system and distanced 80 cm to the wooden test table. For Radiated Emission Test, one horizontal conductive ground plane extended at least 1m beyond the periphery of the EUT and the largest measuring antenna, and covered the entire area between the EUT and the antenna. It has no holes or gaps having longitudinal dimensions larger than one-tenth of a wavelength at the highest frequency of measurement up to 1GHz.

Site # 3 & # 4 Line Conducted Test Site: At Shielding Room

7 TEST EQUIPMENT LIST (EMISSION)

Instrumentation: The following list contains equipment used at C & C Laboratory, Co., Ltd. for testing. The equipment conforms to the CISPR 16-1 / ANSI C63.2-1988 Specifications for Electromagnetic Interference and Field Strength Instrumentation from 9kHz to 1.0 / 2.0 GHz.

Equipment used during the tests:

Open Area Test Site: # 4

Open Area Test Site # 4					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL. DUE
Spectrum Analyzer	ADVANTEST	R3132	91700456	N/A	N/A
EMI Test Receiver	R&S	ESVS10	846285/016	04/11/2003	04/10/2004
Bilog Antenna	CHASE	CBL 6112B	2462	01/11/2003	01/10/2004
Turn Table	Chance most	N/A	N/A	N.C.R	N.C.R
Antenna Tower	Chance most	N/A	N/A	N.C.R	N.C.R
Controller	Chance most	N/A	N/A	N.C.R	N.C.R
RF Switch	ANRITSU	MP59B	M51067	N.C.R	N.C.R
Site NSA	C&C Lab.	N/A	N/A	08/17/2002	08/16/2003
Decoupling Network	FISCHER CUSTOM COMMUNICATION INC.	F-201-DCN-5-6MM	12	04/21/2003	04/21/2004

Conducted Emission Test Site: # 4

Conducted Emission Test Site # 4					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL. DUE
EMI Test Receiver	R&S	ESCS30	845552/030	02/18/2003	02/17/2004
LISN	R&S	ENV 4200	830326/016	03/05/2003	03/04/2004
LISN	EMCO	3825/2	9003/1382	02/26/2003	02/25/2004
2X2 WIRE ISN	R&S	ENY22	100020	06/20/2003	06/19/2004
FOUR WIRE ISN	R&S	ENY41	100006	06/20/2003	06/19/2004

Power Harmonic & Voltage Fluctuation/Flicker:

Power Harmonic & Voltage Fluctuation/Flicker Measurement (61000-3-2&-3-3)					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL. DUE.
Harmonic & Flicker Tester	HAEFELY TRENCH	PHF555	080 419-25	10/14/2002	10/13/2003

The calibrations of the measuring instruments, including any accessories that may effect such calibration, are checked frequently to assure their accuracy. Adjustments are made and correction factors applied in accordance with instructions contained in the manual for the measuring instrument.

8 TEST EQUIPMENT LIST (IMMUNITY)

ESD test (61000-4-2)					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
ESD Generator	SCHAFFNER	NSG438	170	04/24/2003	04/23/2004
Radiated Electromagnetic Field immunity Measurement (61000-4-3)					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
S.G.	R&S	SMY02	100094	08/08/2002	08/07/2003
Power Amplifier	ar	150W1000	300300	N/A	N/A
Power Antenna	EMCO	93141	9712-1083	N/A	N/A
Fast Transients/Burst test (61000-4-4)					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Fast Transients/Burst Generator	HAEFELY TRENCH	PEFT-JUNIOR	583 333-117	08/22/2002	08/21/2003
Clamp	HAEFELY TRENCH	093 506.1	080 421.13	N/A	N/A
Surge Immunity test (61000-4-5)					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Surge Tester	HAEFELY TRENCH	PSUGER 4010	583 334-71	09/03/2002	09/02/2003
CS test (61000-4-6)					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
S.G.	R&S	SMY02	100094	08/08/2002	08/07/2003
Power Amplifier	ar	500A100A	300299	N/A	N/A
CDN	Lüthi	801-M3	1879	02/26/2003	02/25/2004
CDN	MEB	M2	A3002010	04/28/2003	04/27/2004
CDN	SCHAFFNER	T400	16906	10/17/2002	10/16/2003
Power Frequency Magnetic Field Immunity test (61000-4-8)					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
TRIAX ELF Magnetic Field Meter	F.W.BELL	4090	9711	10/21/2002	10/20/2003
Clamp Meter	National	300K	11-5980 K	11/19/2002	11/18/2003
Magnetic Field Tester	HAEFELY TRENCH	MAG 100.1	080 938-01	N/A	N/A
Voltage Dips/Short Interruption and Voltage Variation Immunity test (61000-4-11)					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Dips/Interruption and Variations Simulator	HAEFELY TRENCH	PLINE 1610	080 344-05	03/28/2003	03/27/2004

9 SECTION 1 EN 55022 (LINE CONDUCTED & RADIATED EMISSION)

9.1 MEASUREMENT PROCEDURE (PRELIMINARY LINE CONDUCTED EMISSION TEST)

- 1) The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per EN 55022 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2) Support equipment, if needed, was placed as per EN 55022.
- 3) All I/O cables were positioned to simulate typical actual usage as per EN 55022.
- 4) The EUT received AC power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5) All support equipment received power from a second LISN supplying power of 110VAC/60Hz, if any.
- 6) The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7) Analyzer / Receiver scanned from 150kHz to 30MHz for emissions in each of the test modes.
- 8) During the above scans, the emissions were maximized by cable manipulation.
- 9) The following test mode(s) were scanned during the preliminary test:

Mode(s):

1. 1280 × 1024 Resolution (100Mbps)
 2. 1280 × 1024 Resolution (10Mbps)
 3. 1024 × 768 Resolution (100Mbps)
 4. 800 x 600 Resolution (100Mbps)
 5. 640 × 480 Resolution (100Mbps)
 6. S-Video Out (100Mbps)
- 10) After the preliminary scan, we found the following test mode producing the highest emission level.

Mode: 1.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

MEASUREMENT PROCEDURE (FINAL LINE CONDUCTED EMISSION TEST)

- 1) EUT and support equipment was set up on the test bench as per step 10 of the preliminary test.
- 2) A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less -2dB to the A.V. limit in Q.P. mode, then the emission signal was re-checked using an A.V. detector.
- 3) The test data of the worst case condition(s) was reported on the Summary Data page.

Data Sample:

Freq. MHz	Q.P. Raw dBuV	Average Raw dBuV	Q.P. Limit dBuV	Average Limit dBuV	Q.P. Margin dB	Average Margin dB	Note
x.xx	43.95	---	56	46	-12.05	---	L1

Freq.	= Emission frequency in MHz
Raw dBuV	= Uncorrected Analyzer/Receiver reading + Insertion loss of LISN, if it > 0.5 dB
Limit dBuV	= Limit stated in standard
Margin dB	= Reading in reference to limit
Note	= Current carrying line of reading
“---”	= The emission level complied with the Average limits, with at least 2dB margin limits, so no further recheck.

Calculation example:

$$\text{Margin (dB)} = \text{RAW (dBuV)} - \text{Limit (dBuV)}$$

LINE CONDUCTED EMISSION LIMIT (EN 55022)

Frequency	Maximum RF Line Voltage	
	Q.P.	AVERAGE
150kHz-500kHz	66-56dBuV	56-46dBuV
500kHz-5MHz	56dBuV	46dBuV
5MHz-30MHz	60dBuV	50dBuV

Note: The lower limit shall apply at the transition frequency.

9.2 MEASUREMENT PROCEDURE (COMMON MODE CONDUCTED EMISSION MEASUREMENT)

- 1) Selecting ISN for unscreened cable or a current probe for screened cable to take measurement.
- 2) The port of the EUT was connected to the remote side support equipment through the ISN/Current Probe and communication in normal condition.
- 3) Making a overall range scan by using the test receiver controlled by controller and record at least six highest emissions for showing in the test report.
- 4) Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.
- 5) In case of measuring on the screened cable, the current limit shall be applied; otherwise the voltage limit should be applied.
- 6) The test data of the worst case condition(s) was reported on the Summary Data page.

Data Sample:

Freq. MHz	Q.P. Raw dBuV	Average Raw dBuV	Q.P. Limit dBuV	Average Limit dBuV	Q.P. Margin dB	Average Margin dB	Note
x.xx	43.95	---	74	64	-30.05	---	

Freq.	= Emission frequency in MHz
Raw dBuV	= Uncorrected Analyzer / Receiver reading
Limit dBuV	= Limit stated in standard
Margin dB	= Reading in reference to limit
Note	= Current carrying line of reading
“---“	= The emission level complied with the Average limits, with at least 2 dB margin, so no further recheck.

COMMON MODE CONDUCTED EMISSION LIMIT AT TELECOMMUNICATION PORTS

<input checked="" type="checkbox"/> CE-Mark (EN 55022:1998)					
CLASS	Measuring Band	Voltage limit dB(uV)		Current limit dB(uA)	
		Q.P.	AV	Q.P.	AV
B	150kHz-500kHz	84-74	74-64	40-30	30-20
	500kHz-30MHz	74	64	30	20

Note: The lower limit shall apply at the transition frequency.

9.3 MEASUREMENT PROCEDURE (PRELIMINARY RADIATED EMISSION TEST)

- 1) The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden turntable with a height of 0.8 meters is used which is placed on the ground plane as per EN 55022 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2) Support equipment, if needed, was placed as per EN 55022.
- 3) All I/O cables were positioned to simulate typical actual usage as per EN 55022.
- 4) The EUT received AC power source from the outlet socket under the turntable. All support equipment received 110VAC/60Hz power from another socket under the turntable, if any.
- 4.1 Mains cables, telephone lines or other connections to auxiliary equipment located outside the test are shall drape to the floor, be fitted with ferrite clamps or ferrite tubes placed on the floor at the point where the cable reaches the floor and then routed to the place where they leave the turntable. No. extension cords shall be used to mains receptacle.
- 5) The antenna was placed at 10 meter away from the EUT as stated in EN 55022. The antenna connected to the Analyzer via a cable and at times a pre-amplifier would be used.
- 6) The Analyzer / Receiver quickly scanned from 30MHz to 1000MHz. The EUT test program was started. Emissions were scanned and measured rotating the EUT to 360 degrees and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- 7) The following test mode(s) were scanned during the preliminary test:

Mode(s):

1. **1280 × 1024 Resolution (100Mbps)**
 2. **1280 × 1024 Resolution (10Mbps)**
 3. **1024 × 768 Resolution (100Mbps)**
 4. **800 × 600 Resolution (100Mbps)**
 5. **640 × 480 Resolution (100Mbps)**
 6. **S-Video Out (100Mbps)**
- 8) After the preliminary scan, we found the following test mode producing the highest emission level.

Mode: 1.

Then, the EUT and cable configuration, antenna position, polarization and turntable position of the above highest emission level were recorded for final testing.

MEASUREMENT PROCEDURE (FINAL RADIATED EMISSION TEST)

- 1) EUT and support equipment were set up on the turntable as per step 8 of the preliminary test.
- 2) The Analyzer / Receiver scanned from 30MHz to 1000MHz. Emissions were scanned and measured rotating the EUT to 360 degrees, varying cable placement and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- 3) Recorded at least the six highest emissions. Emission frequency, amplitude, antenna position, polarization and turntable position were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit and only Q.P. reading is presented.
- 4) The test data of the worst case condition(s) was reported on the Summary Data page.

Data Sample:

Freq. (MHz)	Raw Data (dBuV)	Corr. Factor (dB/m)	Emiss. Level (dBuV/m)	Limits	Margin (dB)
xx.xx	14.0	11.2	26.2	30	-3.8

Freq.	= Emission frequency in MHz
Raw Data (dBuV)	= Uncorrected Analyzer / Receiver reading
Corr. Factor (dB/m)	= Antenna factor + Cable loss – Amplifier gain
Emiss. Level (dBuV/m)	= Raw reading converted to dBuV/m and CF added
Limit (dBuV/m)	= Limit stated in standard
Margin (dB)	= Reading in reference to limit
P	= Peak Reading
Q	= Quasi-peak Reading
A	= Average Reading

Calculation example:

$$\text{Margin (dB)} = \text{Emiss. Level (dBuV/m)} - \text{Limits (dBuV/m)}$$

$$\text{Emission Level (dBuV/m)} = \text{Raw Data (dBuV)} + \text{Corr Factor (dB/m)}$$

RADIATED EMISSION LIMIT

Frequency (MHz)	Distance (m)	Maximum Field Strength Limit (dBuV/m/ Q.P.)
30-230	10	30
230-1000	10	37

Note: The lower limit shall apply at the transition frequency.

10 BLOCK DIAGRAM OF TEST SETUP


System Diagram of Connections between EUT and Simulators

EUT: Panel PC

Trade Name: ADVANTECH

Model Number: PPC-174T

Power Cord: Unshielded, 1.8m



11 SUMMARY DATA

(LINE CONDUCTED TEST)

Model Number: PPC-174T

Location: Site # 4

Tested by: Arno Hsieh

Test Mode: Mode 1

Test Results: Passed

Temperature: 28°C

Humidity: 63%RH

(The chart below shows the highest readings taken from the final data)

FREQ MHz	Q.P. RAW dBuV	AVG RAW dBuV	Q.P. Limit dBuV	AVG Limit dBuV	Q.P. Margin dB	AVG Margin dB	NOTE
0.205	43.20	---	63.40	53.40	-20.20	---	L1
0.973	38.30	---	56.00	46.00	-17.70	---	L1
2.633	32.80	---	56.00	46.00	-23.20	---	L1
4.092	40.50	---	56.00	46.00	-15.50	---	L1
6.722	36.40	---	60.00	50.00	-23.60	---	L1
7.903	39.80	---	60.00	50.00	-20.20	---	L1
0.207	44.30	---	63.30	53.30	-19.00	---	L2
0.977	39.20	---	56.00	46.00	-16.80	---	L2
2.433	38.40	---	56.00	46.00	-17.60	---	L2
4.097	39.20	---	56.00	46.00	-16.80	---	L2
6.523	40.40	---	60.00	50.00	-19.60	---	L2
7.566	39.20	---	60.00	50.00	-20.80	---	L2

L1 = Line One (Hot side) / L2 = Line Two (Neutral side)

****NOTE:** “---” denotes the emission level was or more than 2dB below the Average limit,
so no re-check anymore.

SUMMARY DATA

(COMMON MODE CONDUCTED EMISSION MEASUREMENT)

(LAN Port)

Model Number: PPC-174T

Location: Site # 4

Tested by: Arno Hsieh

Test Mode: Mode 1

Test Results: Passed

Temperature: 28°C

Humidity: 63%RH

(The chart below shows the highest readings taken from the final data)

FREQ MHz	Q.P. RAW dBuV	AVG RAW dBuV	Q.P. Limit dBuV	AVG Limit dBuV	Q.P. Margin dB	AVG Margin dB	NOTE
0.150	65.00	---	84.00	74.00	-19.00	---	10Base
2.500	50.20	---	74.00	64.00	-23.80	---	10Base
6.600	52.30	---	74.00	64.00	-21.70	---	10Base
7.187	53.60	---	74.00	64.00	-20.40	---	10Base
9.250	54.10	---	74.00	64.00	-19.90	---	10Base
11.887	53.90	---	74.00	64.00	-20.10	---	10Base
10.058	58.20	---	74.00	64.00	-15.80	---	100Base
14.146	57.80	---	74.00	64.00	-16.20	---	100Base
23.119	61.20	---	74.00	64.00	-12.80	---	100Base
24.351	60.00	---	74.00	64.00	-14.00	---	100Base
26.608	60.60	---	74.00	64.00	-13.40	---	100Base
27.155	58.20	---	74.00	64.00	-15.80	---	100Base

SUMMARY DATA

(RADIATED EMISSION TEST)

Model Number: PPC-174T

Location: Site # 4

Tested by: George Liao

Polar: Vertical--10m

Test Mode: Mode 1

Test Results: Passed

Detector Function: Quasi-Peak

Temperature: 28°C

Humidity: 63%RH

(The chart below shows the highest readings taken from the final data)

Freq. (MHz)	Raw Data (dBuV)	Corr. Factor (dB/m)	Emiss. Level (dBuV/m)	Limits	Margin (dB)
135.02	11.8	14.2	26.0	30.0	-4.0
168.77	7.5	12.9	20.4	30.0	-9.6
178.00	6.7	12.3	19.0	30.0	-11.0
202.00	13.5	12.7	26.2	30.0	-3.8
208.80	12.5	12.8	25.3	30.0	-4.7
480.00	6.4	22.4	28.8	37.0	-8.2

SUMMARY DATA

(RADIATED EMISSION TEST)

Model Number: PPC-174T

Location: Site # 4

Tested by: George Liao

Polar: Horizontal--10m

Test Mode: Mode 1

Test Results: Passed

Detector Function: Quasi-Peak

Temperature: 28°C

Humidity: 63%RH

(The chart below shows the highest readings taken from the final data)

Freq. (MHz)	Raw Data (dBuV)	Corr. Factor (dB/m)	Emiss. Level (dBuV/m)	Limits	Margin (dB)
135.04	6.5	14.2	20.7	30.0	-9.3
166.52	3.7	13.0	16.7	30.0	-13.3
176.26	13.0	12.4	25.4	30.0	-4.6
231.00	10.5	13.7	24.2	37.0	-12.8
366.00	6.3	18.9	25.2	37.0	-11.8
477.60	6.3	22.3	28.6	37.0	-8.4

12 SECTION 2 EN 61000-3-2 & EN 61000-3-3 (POWER HARMONICS & VOLTAGE FLUCTUATION / FLICKER)


POWER HARMONICS MEASUREMENT

Port : AC mains
Basic Standard : EN 61000-3-2 (1995 + A1: 1998 + A2: 1998)
Limits : ☒ CLASS A ; ☐ CLASS D
Tester : Lung Tsai
Temperature : 25°C
Humidity : 51%
Input Current Wave : Without special wave shape

VOLTAGE FLUCTUATION/FLICKER MEASUREMENT

Port : AC mains
Basic Standard : EN 61000-3-3 (1995)
Limits : § 5 of EN 61000-3-3
Tester : Lung Tsai
Temperature : 25°C
Humidity : 51%

Block Diagram of Test Setup:



Result:

Please see the attached test data.

EN 61000-3-2 TEST REPORT 2003/6/19 01:38 PM

Unit: Panel PC

Model No.: PPC-174T

Remarks: Temp: 25°C Humid: 51%

Operator: Lung Tsai

=====

TEST SETUP

Test Freq.:	50.00 Hz.	Test Voltage:	230.0 vac
Waveform :	SINE	Test Time:	2.5 min.
Classification :	CLASS A	Test Type:	STEADY-STATE

Prog. Zo Enabled:	YES	Prog. Zo:	0.000
-------------------	-----	-----------	-------

Motor Driven with Phase Angle Control:	NO
Impedance selected:	DIRECT

Synthetic R+L Enabled:	NO		
Resistance:	0.380 Ohms	Inductance:	460.000 uH

MAX WATTS:103.2W

TEST DATA

Result: PASS

Harmonic Current Results

Hn	AMPS	LO Limit	HI Limit	Result
0	0.000	0.000	0.000	PASS
1	0.669	NaN	NaN	PASS
2	0.003	1.080	1.080	PASS
3	0.108	2.300	2.300	PASS
4	0.001	0.430	0.430	PASS
5	0.013	1.140	1.140	PASS
6	0.001	0.300	0.300	PASS
7	0.018	0.770	0.770	PASS
8	0.000	0.230	0.230	PASS
9	0.006	0.400	0.400	PASS
10	0.000	0.184	0.184	PASS
11	0.008	0.330	0.330	PASS
12	0.000	0.153	0.153	PASS
13	0.007	0.210	0.210	PASS
14	0.000	0.131	0.131	PASS
15	0.009	0.150	0.150	PASS
16	0.001	0.115	0.115	PASS
17	0.012	0.132	0.132	PASS
18	0.000	0.102	0.102	PASS
19	0.007	0.118	0.118	PASS
20	0.000	0.092	0.092	PASS

21	0.007	0.107	0.107	PASS
22	0.000	0.084	0.084	PASS
23	0.007	0.098	0.098	PASS
24	0.001	0.077	0.077	PASS
25	0.009	0.090	0.090	PASS
26	0.001	0.071	0.071	PASS
27	0.010	0.083	0.083	PASS
28	0.001	0.066	0.066	PASS
29	0.016	0.078	0.078	PASS
30	0.001	0.061	0.061	PASS
31	0.010	0.073	0.073	PASS
32	0.001	0.058	0.058	PASS
33	0.004	0.068	0.068	PASS
34	0.001	0.054	0.054	PASS
35	0.010	0.064	0.064	PASS
36	0.001	0.051	0.051	PASS
37	0.005	0.061	0.061	PASS
38	0.001	0.048	0.048	PASS
39	0.006	0.058	0.058	PASS
40	0.001	0.046	0.046	PASS

END OF REPORT

EN 61000-3-3 TEST REPORT 2003/6/19 01:19 PM

Unit: Panel PC

Model No.: PPC-174T (Continue)

Remarks: Temp: 25°C Humid: 51%

Operator: Lung Tsai

=====

TEST SETUP

Test Freq.: 50.00 Hz. Test Voltage: 230.0 vac

Waveform : SINE

Test Time: 10.0 min. Tshort: 10.0 min.

Prog. Zo Enabled: YES Prog. Zo: 0.000

Voltage Change less than once per Hour: NO

Impedance selected: DIRECT

Synthetic R+L Enabled: NO

Resistance: 0.380 Ohms Inductance: 460.000 uH

TEST DATA

Result: PASS

	EUT Data	Limit	Result	Test Enabled
Pst max	0.001	1.00	PASS	true
Plt max	0.001	0.65	PASS	true
dc %	0.00	3.00	PASS	true
dmax %	0.00	4.00	PASS	true
d(t) sec.	0.00	0.20	PASS	true

Power Source Data

Source Pst max	0.020	0.400	PASS	true
% THD	0.03	3.00	PASS	true

END OF REPORT

EN 61000-3-3 TEST REPORT 2003/6/19 01:33 PM

Unit: Panel PC

Model No.: PPC-174T (Manual Switch)

Remarks: Temp: 25°C Humid: 51%

Operator: Lung Tsai

=====

TEST SETUP

Test Freq.: 50.00 Hz. Test Voltage: 230.0 vac

Waveform : SINE

Test Time: 10.0 min. Tshort: 10.0 min.

Prog. Zo Enabled: YES Prog. Zo: 0.000

Voltage Change less than once per Hour: NO

Impedance selected: DIRECT

Synthetic R+L Enabled: NO

Resistance: 0.380 Ohms Inductance: 460.000 uH

TEST DATA

Result: PASS

	EUT Data	Limit	Result	Test Enabled
Pst max	0.021	1.00	PASS	true
Plt max	0.021	0.65	PASS	true
dc %	0.00	3.00	PASS	true
dmax %	0.00	4.00	PASS	true
d(t) sec.	0.00	0.20	PASS	true

Power Source Data

Source Pst max	0.020	0.400	PASS	true
% THD	0.03	3.00	PASS	true

END OF REPORT


13 SECTION 3 IEC 61000-4-2 (ELECTROSTATIC DISCHARGE)

ELECTROSTATIC DISCHARGE (ESD) IMMUNITY TEST

Port	: Enclosure
Basic Standard	: IEC 61000-4-2
Test Level	: ± 8 kV (Air Discharge) ± 4 kV (Contact Discharge) ± 4 kV (Indirect Discharge)
Performance Criteria	: B (Standard Require)
Tester	: Lung Tsai
Temperature	: 26°C
Humidity	: 46%
Pressure	: 1016mbar

Block Diagram of Test Setup:

(The 470 k ohm resistors are installed per standard requirement)



Test Procedure:

1. The EUT was located 0.1 m minimum from all side of the HCP.
2. The indirect support units were located 1 m minimum away from the EUT, but direct support unit was/were located at same location as EUT on the HCP and keep at a distance of 10 cm with EUT.
3. A scroll 'H' test program was loaded and executed in Windows 2000 mode.
4. The EUT sent above message to LCD Panel of EUT and related peripherals through the test.
5. Active the communication function if the EUT with such port(s).
6. As per the requirement of EN 55024; applying direct contact discharge at the sides other than front of EUT at minimum 50 discharges (25 positive and 25 negative) if applicable, can't be applied direct contact discharge side of EUT then the indirect discharge shall be applied. One of the test points shall be subjected to at least 50 indirect discharge (contact) to the front edge of horizontal coupling plane.
7. Other parts of EUT where it is not possible to perform contact discharge then selecting appropriate points of EUT for air discharge, a minimum of 10 single air discharges shall be applied.
8. The application of ESD to the contact of open connectors is not required.
9. The EUT direct connection units also need to be applied ESD at the port of EUT cable connected.
10. Putting a mark on EUT to show tested points. The following test condition was followed during the tests.

Note: As per IEC 61000-4-2:2001, with two 470k bleed resistors cable is connected between the EUT and HCP during the test applicable for power ungrounded or battery operating unit only.

The electrostatic discharges were applied as follows:

Amount of Discharges	Voltage	Coupling	Result (Pass/Fail)
Mini 10 /Point	± 8 kV	Air Discharge	Pass
Mini 25 /Point	± 4 kV	Contact Discharge	Pass
Mini 25 /Point	± 4 kV	Indirect Discharge HCP (Front)	Pass
Mini 25 /Point	± 4 kV	Indirect Discharge VCP (Right)	N/A
Mini 25 /Point	± 4 kV	Indirect Discharge VCP (Left)	N/A
Mini 25 /Point	± 4 kV	Indirect Discharge VCP (Back)	N/A

****The tested points to EUT, please refer to attached page.**

(Blue arrow mark for Contact Discharge and red arrow mark for Air Discharge)

Performance & Result:

- ☒ **Criteria A:** The apparatus continues to operate as intended. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance.
- ☐ **Criteria B:** The apparatus continues to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed.
- ☐ **Criteria C:** Temporary loss of function is allowed, provided the functions self recoverable or can be restored by the operation of controls.

<input checked="" type="checkbox"/> PASS	<input type="checkbox"/> FAILED
Observation: No any function degraded during the tests.	

The Tested Points of EUT

Photo 1 of 5



Photo 2 of 5




Photo 3 of 5



Photo 4 of 5



Photo 5 of 5




14 SECTION 4 IEC 61000-4-3 (RADIATED ELECTROMAGNETIC FIELD)

RADIATED ELECTROMAGNETIC FIELD IMMUNITY TEST

Port	: Enclosure
Basic Standard	: IEC 61000-4-3
Requirements	: 3 V/m / with 80% AM. 1kHz Modulation.
Performance Criteria	: A (Standard Require)
Tester	: Lung Tsai
Temperature	: 26°C
Humidity	: 46%
Pressure	: 1016mbar

Block Diagram of Test Setup:



Test Procedure:

1. The EUT was located at the edge of supporting table keep 3 meter away from transmitting antenna, it just the calibrated square area of field uniformity. The support units were located outside of the uniformity area, but the cable(s) connected with EUT were exposed to the calibrated field as per IEC 61000-4-3.
2. A scroll 'H' messages were displayed on part of screen of LCD Panel of EUT and an enlarged 'H' characters were displayed on the other part of screen of LCD Panel of EUT.
3. Adjusting the monitoring camera to monitor the 'H' message as clear as possible.
4. Setting the testing parameters of RS test software per IEC 61000-4-3.
5. Performing the test at each side of with specified level from 80MHz to 1000MHz at 1% steps.
6. Recording the test result in following table.
7. It is not necessary to perform test as per annex A of EN 55024:1998 if the EUT doesn't belong to ITE product.

IEC 61000-4-3 Preliminary test conditions:

Test level : 6V/m
Steps : 4 % of fundamental
Dwell Time : 3 sec

Range (MHz)	Field	Modulation	Polarity	Position (°)	Result (Pass/Fail)
80-1000	6V/m	Yes	H	Front	Pass
80-1000	6V/m	Yes	V	Front	Pass
80-1000	6V/m	Yes	H	Right	Pass
80-1000	6V/m	Yes	V	Right	Pass
80-1000	6V/m	Yes	H	Back	Pass
80-1000	6V/m	Yes	V	Back	Pass
80-1000	6V/m	Yes	H	Left	Pass
80-1000	6V/m	Yes	V	Left	Pass

IEC 61000-4-3 Final test conditions:

Test level : 3V/m
Steps : 1 % of fundamental
Dwell Time : 3 sec

Range (MHz)	Field	Modulation	Polarity	Position (°)	Result (Pass/Fail)
80-1000	3V/m	Yes	H	Front	Pass
80-1000	3V/m	Yes	V	Front	Pass

Performance & Result:

- ☒ **Criteria A:** The apparatus continues to operate as intended. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance.
- ☐ **Criteria B:** The apparatus continues to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed.
- ☐ **Criteria C:** Temporary loss of function is allowed, provided the functions self recoverable or can be restored by the operation of controls.

☒ **PASS**

☐ **FAILED**


Observation: No any function degraded during the tests.

15 SECTION 5 IEC 61000-4-4 (FAST TRANSIENTS/BURST)

FAST TRANSIENTS/BURST IMMUNITY TEST

Port	: On Power Supply Lines and Data Lines
Basic Standard	: IEC 61000-4-4
Requirements	: ± 1 kV for Power Supply Line ± 0.5 kV to LAN Cable
Performance Criteria	: B (Standard Require)
Tester	: Lung Tsai
Temperature	: 26°C
Humidity	: 46%
Pressure	: 1016mbar

Block Diagram of Test Setup:



Test Procedure:

1. The EUT and support units were located on a wooden table 0.8 m away from ground reference plane.
2. A 1.0 meter long power cord was attached to EUT during the test.
3. The length of communication cable between communication port and clamp was keeping within 1 meter.
4. A test program was loaded and executed in Windows 2000 mode.
5. The data was sent to LCD Panel of EUT filling the screens with upper case of "H" patterns.
6. The test program exercised related support units sequentially.
7. Repeating step 3 to 6 through the test and increase test voltage to the EUT ports from minimum to standard request or client request.
8. Recording the test result as shown in following table.

Test conditions:

Impulse Frequency : 5kHz

Tr/Th : 5/50ns

Burst Duration : 15ms

Burst Period : 3Hz

Inject Line	Voltage kV	Inject Method	Result (Pass/Fail)
L	± 1	Direct	Pass
N	± 1	Direct	Pass
PE	± 1	Direct	Pass
L + N	± 1	Direct	Pass
L + PE	± 1	Direct	Pass
N + PE	± 1	Direct	Pass
L + N + PE	± 1	Direct	Pass
LAN Cable	± 0.5	Clamp	Pass

Performance & Result:

- ☒ **Criteria A:** The apparatus continues to operate as intended. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance.
- ☐ **Criteria B:** The apparatus continues to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed.
- ☐ **Criteria C:** Temporary loss of function is allowed, provided the functions self recoverable or can be restored by the operation of controls.

☒ **PASS**

☐ **FAILED**


Observation: No any function degraded during the tests.

16 SECTION 6 IEC 61000-4-5 (SURGE IMMUNITY)

SURGE IMMUNITY TEST

Port	: Power Cord
Basic Standard	: IEC 61000-4-5
Requirements	: ± 1 kV (Line to Line) ± 2 kV (Line to Ground)
Performance Criteria	: B (Standard Require)
Tester	: Lung Tsai
Temperature	: 26°C
Humidity	: 46%
Pressure	: 1016mbar

Block Diagram of Test Setup:



Test Procedure:

1. The EUT and support units were located on a wooden table 0.8 m away from ground floor.
2. A test program was loaded and executed in Windows 2000 mode.
3. The data was sent to LCD Panel of EUT filling the screens with upper case of "H" patterns.
4. The test program exercised related support units sequentially.
5. Repeating step 3 to 4 through the test and increase test voltage to the EUT ports from minimum to standard request or client request.
6. Recording the test result as shown in following table.

Test conditions:

Voltage Waveform : 1.2/50 *us*
Current Waveform : 8/20 *us*
Polarity : Positive/Negative
Phase angle : 0°, 90°, 270°
Number of Test : 5

Coupling Line	Voltage (kV)	Polarity	Coupling Method	Result (Pass/Fail)
L1-L2	1	Positive	Capacitive	Pass
L1-PE	2	Positive	Capacitive	Pass
L2-PE	2	Positive	Capacitive	Pass
L1-L2	1	Negative	Capacitive	Pass
L1-PE	2	Negative	Capacitive	Pass
L2-PE	2	Negative	Capacitive	Pass

Performance & Result:

- ☒ **Criteria A:** The apparatus continues to operate as intended. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance.
- ☐ **Criteria B:** The apparatus continues to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed.
- ☐ **Criteria C:** Temporary loss of function is allowed, provided the functions self recoverable or can be restored by the operation of controls.

<input checked="" type="checkbox"/> PASS <input type="checkbox"/> FAILED
Observation: No any function degraded during the tests.


17 SECTION 7 IEC 61000-4-6 (CONDUCTED DISTRBANCE/INDUCED RADIO-FREQUENCY FIELD)

CONDUCTED DISTRBANCE/INDUCED RADIO-FREQUENCY FIELD IMMUNITY TEST


Port	: AC Port and LAN Cable
Basic Standard	: IEC 61000-4-6
Requirements	: 3V with 80% AM. 1kHz Modulated
Injection Method	: CDN-M3 for Power Cord EM-Clamp for LAN Cable
Performance Criteria	: A (Standard Require)
Tester	: Lung Tsai
Temperature	: 26°C
Humidity	: 46%
Pressure	: 1016mbar

Block Diagram of Test Setup:

Side View:



Top view:



Test Procedure:

1. The Host PC and support units were located at a ground reference plane with the interposition of a 0.1 m thickness insulating support and the CDN was located on GRP directly.
2. A 'H' messages were displayed on screen of LCD Panel of EUT.
3. Adjusting the monitoring camera to monitor the 'H' message as clear as possible.
4. Setting the testing parameters of CS test software per IEC 61000-4-6.
5. Recording the test result in following table.

Test conditions:

Frequency Range : 0.15MHz-80MHz

Frequency Step : 1% of fundamental

Dwell Time : 3 sec

Range (MHz)	Field	Modulation	Result (Pass/Fail)
0.15-80	3V	Yes	Pass

Performance & Result:

- ☒ **Criteria A:** The apparatus continues to operate as intended. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance.
- ☐ **Criteria B:** The apparatus continues to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed.
- ☐ **Criteria C:** Temporary loss of function is allowed, provided the functions self recoverable or can be restored by the operation of controls.


<input checked="" type="checkbox"/> PASS <input type="checkbox"/> FAILED
Observation: No any function degraded during the tests.

18 SECTION 8 IEC 61000-4-8 (POWER FREQUENCY MAGNETIC FIELD IMMUNITY TEST)

POWER FREQUENCY MAGNETIC FIELD IMMUNITY TEST

Port : Enclosure
Basic Standard : IEC 61000-4-8
Requirements : 1 A/m
Performance Criteria : A (Standard Require)
Tester : Lung Tsai
Temperature : 26°C
Humidity : 46%
Pressure : 1016mbar

Block Diagram of Test Setup:



Test Procedure:

1. The EUT and support units were located on Ground Reference Plane with the interposition of a 0.1 m thickness insulation support.
2. Putting the induction coil on horizontal direction.(X direction)
3. A test program was loaded and executed in Windows 2000 mode.
4. The data was sent to the screen of LCD Panel of EUT and filling the screen with upper case of "H" patterns.
5. The test program exercised related support units sequentially.
6. Repeating step 3 to 5 through the test.
7. Recording the test result as shown in following table.
8. Rotating the induction coil by 90° (Y direction) then repeat step 3 to 7.
9. Rotating the induction coil by 90° again (Z direction) then repeat step 3 to 7.

*. Test conditions:

Field Strength: 1A/m
Power Freq.: 50Hz
Orientation: X, Y, Z

Orientation	Field	Result (Pass/Fail)	Remark
X	1A	Pass	
Y	1A	Pass	
Z	1A	Pass	

Performance & Result:

- ☒ **Criteria A:** The apparatus continues to operate as intended. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance.
- ☐ **Criteria B:** The apparatus continues to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed.
- ☐ **Criteria C:** Temporary loss of function is allowed, provided the functions self recoverable or can be restored by the operation of controls.

☒ **PASS**

☐ **FAILED**

Observation: No any function degraded during the tests.

19 SECTION 9 IEC 61000-4-11 (VOLTAGE DIPS, SHORT INTERRUPTIONS AND VOLTAGE VARIATIONS)

VOLTAGE DIPS / SHORT INTERRUPTIONS


Port : AC mains
Basic Standard : IEC 61000-4-11 (1994)
Requirement : PHASE ANGLE 0, 45, 90, 135, 180, 225, 270, 315 degrees

Voltage Dips	Test Level % U_T	Reduction (%)	Duration (periods)	Performance Criteria
	<5	>95	0.5	B
	70	30	25	C

Voltage Interceptions	Test Level % U_T	Reduction (%)	Duration (periods)	Performance Criteria
	<5	>95	250	C

Test Interval : Min. 10 sec.
Tester : Lung Tsai
Temperature : 26°C
Humidity : 46%
Pressure : 1016mbar

Block Diagram of Test Setup:



Test Procedure:

1. The EUT and support units were located on a wooden table, 0.8 m away from ground floor.
2. A test program was loaded and executed in Windows 2000 mode.
3. The data was sent to LCD Panel of EUT filling the screens with upper case of "H" patterns.
4. The test program exercised related support units sequentially.
5. Setting the parameter of tests and then Perform the test software of test simulator.
6. Conditions changes to occur at 0 degree crossover point of the voltage waveform.
7. Repeating step 3 to 4 through the test.
8. Recording the test result in test record form.

Test conditions:

The duration with a sequence of three dips/interruptions with interval of 10 s minimum
(Between each test event)

Voltage Dips:

Test Level % U_T	Reduction (%)	Duration (periods)	Observation	Meet Performance Criteria
0	100	0.5	Normal	A
70	30	25	Normal	A

Voltage Interruptions:

Test Level % U_T	Reduction (%)	Duration (periods)	Observation	Meet Performance Criteria
0	100	250	EUT shut down but can be recovered by manual, as the events disappear.	C

Normal: No any functions degrade during and after the test.

Performance & Result:

- Criteria A:** The apparatus continues to operate as intended. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance.
- Criteria B:** The apparatus continues to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed.
- Criteria C:** Temporary loss of function is allowed, provided the functions self recoverable or can be restored by the operation of controls.



PASS



FAILED

20 APPENDIX 1 PHOTOGRAPHS OF TEST SETUP

20.1 LINE CONDUCTED EMISSION TEST (EN 55022)

Front View



Back View



20.2 COMMON MODE CONDUCTED EMISSION TEST



20.3 RADIATED EMISSION TEST (EN 55022)

Front View



Back View



20.4 POWER HARMONIC & VOLTAGE FLUCTUATION / FLICKER TEST (EN 61000-3-2, EN 61000-3-3)



20.5 ELECTROSTATIC DISCHARGE TEST (IEC 61000-4-2)



20.6 RADIATED ELECTROMAGNETIC FIELD (IEC 61000-4-3)



20.7 FAST TRANSIENTS/BURST TEST (IEC 61000-4-4)



20.8 SURGE IMMUNITY TEST (IEC 61000-4-5)



20.9 CONDUCTED DISTURBANCE, INDUCED BY RADIO-FREQUENCY FIELDS TEST (IEC 61000-4-6)



20.10 POWER FREQUENCY MAGNETIC FIELD IMMUNITY TEST (IEC 61000-4-8)



20.11 VOLTAGE DIPS / INTERRUPTION TEST (IEC 61000-4-11)



21 APPENDIX 2 PHOTOGRAPHS OF EUT

Front View of EUT



Back View of EUT



Left View of EUT



Right View of EUT



I/O Port of EUT

