

EH-3052

SOHO Server



Introduction

Advantech's EH-3052 SOHO Server platform fanless design is perfect for use as a Firewall, Router, DHCP server, email server, or Web server in the small or home office.

Competent Features

The EH-3052 employs an onboard NS GX1-300MHz or 233MHz, Pentium compatible CPU, optional maximum 256 MB system memory and dual 10/100Base-T Ethernet, one port connects to a WAN, to the Internet, and the other connects to a LAN, to the intranet of a small or home office. The EH-3052's one CRT connector, dual USB connectors and one RS-232 COM (an additional one is optional) port provide interfaces for extra storage, control and communication. Furthermore, the EH-3052 is equipped with a compact and durable case whose size is only 228 x 44 x 146 mm (5.75 x 1.73 x 8.98 inches).

Customization

For different applications, the EH-3052 supports a 2.5" hard drive, and CompactFlash of various capacities. Installations can be done easily, either when the EH-3052 is in production at Advantech or when it arrives at your local agent. Most of all, the EH-3052 chassis can be customized to fulfill different customer specific applications and layouts.



Features

- Customizable, robust chassis for both wall mount and desktop settings
- Low-power, fanless NS GX1-300 Pentium-compatible CPU
- Highly expandable with 2 USB ports and 1 or 2 RS-232 serial ports on board
- Two independent 10/100Base-T Ethernet ports

Specifications

- **CPU:** On-board NS GX1-300 MHz or 233 MHz processor
- **BIOS:** AWARD 256 KB Flash memory
- **Chipset:** NS CX 5530
- **System Memory:** One 144-pin SO DIMM socket accepts up to 128 MB SDRAM
- **Storage:** One 2.5" HDD drive (optional) and one CompactFlash (optional)
- **I/O:** 1 x VGA, 1 x RS-232 port (1x RS-232 internal pin-head), 2 x RJ-45 LAN port, 2 x USB port
- **Ethernet Chipset:** Intel 82559 or RealTek 8139C
- **Watchdog timer:** Software enable/disable intervals at 1.6 seconds
- **PC/104 expansion:** 104-pin 16-bit PC/104 module connector
- **Power management:** APM 1.1 compliant power management
- **Power supply:** AC/DC power adapter, DC 5 V input
- **Operating temperature:** 0 ~ 40° C (32 ~ 104° F)
- **Storage temperature:** -20 ~ 75° C (-4 ~ 167° F)
- **Operating humidity:** 5 ~ 95% @ 40° C, non-condensing
- **Storage humidity:** 5 ~ 95%
- **Dimension:** 228 mm x 44 mm x 146 mm (W x H x D)

Ordering Information

- EH-3052I-000:**
SOHO 300 Server with 2LAN(INT)/2USB/VGA/COM
- EH-3052R-000:**
SOHO 300 Server with 2LAN(RLT)/2USB/VGA/COM
- EH-3052RL-000:**
SOHO 233 Server with 2LAN(RLT)/2USB/VGA/COM

Internet Security Platforms

Note: All specifications are subject to change without notice.