

HPC-7480

4U Tower/Rackmount Chassis for EATX Serverboard with 8 Hot-swap Hard Drive Cages

Preliminary



CE FCC RoHS COMPLIANT PRODUCT

Features


- 4U rackmount chassis supports ATX/CEB/EATX motherboard
- Lockable front bezel prevents unauthorized access
- 665 W high efficiency single power supply
- Swappable fan module design facilitates maintenance

Specifications

Processor Support	Supports dual, single Intel / AMD processors	
Form Factor Support	4U chassis support for max. motherboard size - 12" x 13" EATX	
Expansion Slots	7 x Full-height, Full-length PCI expansion slots	
Drive Bay	Slim ODD Bay	-
	5.25" (front-accessible)	3
	3.5" (front-accessible)	8
	3.5" (internal)	-
	2.5" (front-accessible)	-
Cooling	Chassis Fan	4 (8 cm / CFM)
	Air Filter	Yes
System Monitoring	Chassis intrusion switch	
Front I/O Interface	USB	2
	PS/2	-
Miscellaneous	LED Indicators	Power, HDD activity, LAN
	Rear Panel	-
Environment	Temperature	Operating: 0 ~ 40° C (32 ~ 104° F) Non-Operating: -40 ~ 70° C (-40 ~ 158° F)
	Humidity	10 ~ 85% @ 40° C non-condensing 10 ~ 95% @ 40° C, non-condensing
	Vibration (5-500 Hz)	1 Grms 2 G
	Shock	10 G 30 G
		(with 11 ms duration, half sine wave)
Physical Characteristics	Dimensions (W x H x D)	452 x 178 x 648 mm (4U)
	Weight	29.94 kg

Dimensions

Unit: mm (inch)



Ordering Information

Part Number	Power Supply
HPC-7480-66A1E	665 W Single Power Supply

Packing List

Description	Quantity
665 W Single Power Supply	x 1
Hot-swap 3.5" HDD Trays	x 8
SATA2 Backplane (SAS Backplane Optional)	x 1
Front I/O Panel Board	x 1
Front Bezel with Key (Lockable)	x 1
System Hot-swap Cooling Fans	x 4
Startup Manual	x 1

Front View



Interior View



Rear View

