RMD-1150

1U Rackmount LCD Display with KVM Switch/Keyboard/Touch Pad



Features

- 15" active TFT LCD display with RGB analog output
- Supports 8 IBM PC-compatible computer ports
- Auto Scan from OSD display
- Hot-key functions allow easy computer access
- Supports both PS/2 and serial mouse
- High VGA resolution 1600 x 1200 for external console
- · Selectable user timeout
- EIA 19" rackmount and rugged slide rail
- Operating system independent, transparent to all applications
- Password security locks computer from unauthorized access

Introduction

RMD consists of a keyboard, 15" TFT LCD display, and touch pad. You can control and access multiple computers from a central user console. It saves hundreds of dollars in equipment, space and power costs. There is no need to have additional peripherals for each computer. The administrator can access multiple computers from one location

instead of having to move from one computer to another. Installation is as simple as connecting cables between the RMD switch and your computers. This is ideal for an Internet data center, server room, testing lab, and network-operating center where multiple computers are required.

Specifications and Ordering Information

Part Number		RMD-1150F-8	RMD-1150KM	
		15" XGA TFT	15" XGA TFT	
LCD Display				
LCD Resolution		1024 x 768	1024 x 768	
Computer Port Number		8	1	
Cascade Control PC Number		up to 64	N/A	
On-screen Display (OSD)		Yes		
Front Panel Button control		Yes		
Hot Plug-and-play		Yes	Yes	
Hot-key Control		Yes	N/A	
PC Environment		IBM-Compatible		
Automatic Scan Interval		3, 8, 15, 30 seconds	N/A	
Programmable Scan Patter		Yes	N/A	
External VGA		1600 x 1200 DDC2B		
Computer Keyboard Cable		PS/2 to PS/2		
Computer Mouse Cable		PS/2 to PS/2 or PS/2 to DB-9		
Computer VGA Cable		DB-15 to DB-15 (female to male)		
Computer Keyboard/Mouse/VGA Cable		4 x 1.8 M, 4 x 1 M	1 x 1.8 M	
Console Keyboard Port		PS/2		
Console Mouse Port		PS/2		
Console VGA Port		DB-15		
Dimensions (W x H x D)	mm	436 x 44 x 600		
	inches	17.2 x 1.7 x 23.6		
	size	1 U		
Power Supply (min)		DC 12 V, 4 A		



For More Information



All brand names and registered trademarks are the property of their respective owner All specifications are subject to change without notice Enter