

# UNO-2172

Intel® Pentium® M/Celeron® M  
UNO with 2 x GbE, 4 x COM, DVI

NEW



## Features

- Onboard Pentium® M 1.6 GHz, Celeron® M 1.5 GHz or Celeron M 1.0 GHz
- Onboard 512 KB battery-backup SRAM
- 2 x RS-232 and two RS-232/422/485 ports with automatic flow control
- 2 x 10/100/1000Base-T Ethernet
- DVI-I supports dual display
- Audio with Mic in, Line in, Line out
- Two USB and one type I/II PC Card
- PCI-104 expansion
- Windows® XP Embedded SP2 ready solution
- Supports SATA-1 HDD and external SATA 1.0 devices
- Onboard system status LED indicators
- Supports Wake On LAN and Boot From LAN function
- Fanless and no internal cabling design

## Introduction

UNO-2172 is a high-performance Pentium grade controller that supports PCI-104 expansion, serial communication ports and several other networking interfaces. UNO-2172 supports Windows XP Embedded OS, which offers a pre-configured image with optimized onboard device drivers. Windows XP Embedded delivers the power of the Windows operating system in componentized form. You can seamlessly integrate your applications into Windows XP Embedded and speed up your system development with an application ready platform that can provide a rich networking interface to fulfill diverse requirements.

## Specifications

### General

- **Certifications** CE, FCC class A, UL, CCC
- **Dimensions (W x D x H)** 255 x 152 x 69 mm (10" x 6.0" x 2.7")
- **Enclosure** Aluminum
- **Mounting** Wallmount
- **Power Consumption** 45 W (Typical)
- **Power Input** Min. 48 W (9 ~ 36 V<sub>DC</sub>) (e.g. +24 V @ 2 A), ATX
- **Weight** 3 kg
- **OS Support** Windows XP Embedded, Windows 2000/XP

### System Hardware

- **CPU** Pentium M 1.6 GHz  
Celeron M 1.5 GHz and Celeron 1.0 GHz
- **Memory** 512 MB or 1 GB DDR2 SDRAM
- **Indicators** LEDs for power, IDE, alarm for RAM backup battery
- **Battery Backup SRAM** 512 KB
- **Keyboard/Mouse** 1 x PS/2
- **PC Card** 1 x PC Card slot, supports CardBus (Card-32) Card and 16-bit (PCMCIA 2.1/JEIDA4.2) card  
Supports +5 V, +3.3 V
- **PCI-104** PCI-104 slot, supports +5 & 3.3 V Power
- **Storage** SSD: 1 x internal type I/II CompactFlash® slot  
HDD: 1 x standard 2.5" SATA-1 HDD
- **Display** DVI-I supports DVI and VGA for dual display
- **Audio** Mic in, Line in, Line out
- **SATA** 1 x internal, 1 x external SATA 1.0
- **Watchdog Timer** Programmable

### Communications

- **Serial Ports** 2 x RS-232, 2 x RS-232/422/485 with DB9 connectors  
Automatic RS-485 data flow control
- **Serial Port Speed** RS-232: 50 ~ 115.2 kbps  
RS-422/485: 50 ~ 921.6 kbps (Max.)
- **LAN** 2 x 10/100/1000Base-T Ethernet (supports wake on LAN and built-in boot ROM in flash BIOS)  
RJ45 ports
- **USB Ports** 2 x USB, EHCI, Rev. 2.0 compliant

### Environment

- **Humidity** 95% @ 40° C (non-condensing)
- **Operating Temperature** -20 ~ 50° C (-4 ~ 122° F) @ 5 ~ 85% RH. (for UNO-2172-C22E and UNO-2172-P22E)  
-20 ~ 60° C (-4 ~ 131° F) @ 5 ~ 85% RH. (for UNO-2172-C11E)
- **Shock Protection** IEC 68 2-27  
CompactFlash: 50 G @ wall mount, half sine, 11 ms  
HDD: 20 G @ wall mount, half sine, 11 ms
- **Vibration Protection** IEC 68 2-64 (Random 1 Oct./min, 1hr/axis.)  
CompactFlash: 2 Grms @ 5 ~ 500 Hz,  
HDD: 1 Grms @ 5 ~ 500 Hz

## Ordering Information

- **UNO-2172-C11E** C-M 1.0 G, 512 MB RAM UNO-2172
- **UNO-2172-C22E** C-M 1.5 G, 1 GB RAM UNO-2172
- **UNO-2172-P22E** P-M 1.6 G, 1 GB RAM UNO-2172

### Accessories

- **UNO-PCM22-AE** 2 x PC/104 expansion kit
- **UNO-FPM21-AE** UNO & FPM integration kit