



FKSZ2.E334687

Drivers for Light-emitting-diode Arrays, Modules and Controllers - Component

[Page Bottom](#)

Drivers for Light-emitting-diode Arrays, Modules and Controllers - Component

[See General Information for Drivers for Light-emitting-diode Arrays, Modules and Controllers - Component](#)**MEAN WELL ENTERPRISES CO LTD**

E334687

28 WU-CHUAN 3RD RD
 WUGU INDUSTRIAL PARK
 TAIPEI HSIEN, 248 TAIWAN

LED drivers, Class 2 isolated output, Model CLY-100-Z, where Y can be G (for with Glue) or N (for without Glue), Z can be 12, 15, 20, 24, 27, 36 and 48 for output voltage; Model PLN-100-Z, where Z can be 12, 15, 20, 24, 27, 36 and 48 for output voltage; Models CLG-100-24DLU, CLG-100-24LU.

Model CLY-60-z, where y can be G (with potting compound) or N (without potting compound), z can be 12, 15, 20, 24, 27, 36 and 48 for output voltage; Models PLN-60-z, PLN-45-z, where z can be 12, 15, 20, 24, 27, 36 and 48 for output voltage, without potting compound.

Model HLG-100-YZ Series, where Y can be 20, 24, 30, 36, 42, 48 or 54 for output voltage, and Z can be blank, A or B.

Model HLG-100H-YZ Series, where Y can be 20, 24, 30, 36, 42, 48 or 54 for output voltage, and Z can be blank, A or B.

Isolated Class 2 LED power supplies, Models LPF-60X-YLU, where X may be blank or D, and Y may be 24 or 30 for output voltage.

LED drivers, other than Class 2, Model HLG-240H-yz, where y can be 12, 15, 20, 24, 30, 36, 42, 48, 54, z can be blank, A, B or C; Model: HLG-240-yz, where y can be 12, 15, 20, 24, 30, 36, 42, 48 or 54, z can be blank, A, B or C.

Model HLG-120-XZ Series, where X can be 12, 15, 20, 24, 30, 36, 42, 48 or 54 for output voltage, and Z can be blank, A or B.

Model HLG-120H-XZ Series, where X can be 12, 15, 20, 24, 30, 36, 42, 48 or 54 for output voltage, and Z can be blank, A or B.


Models HLG-150-XZ, HLG-185-YZ Series, where Y can be 12, 15, 20, 24, 30, 36, 42, 48 or 54 for output voltage, and Z can be blank, A or B.

Models HLG-150H-YZ, HLG-185-YZ Series, where Y can be 12, 15, 20, 24, 30, 36, 42, 48 or 54 for output voltage, and Z can be blank, A or B.

Isolated Class 2 LED power supplies, Model CEN-100-X, where X can be 20, 24, 30, 36, 42, 48 and 54 for output voltage.

Model PLY-20-X, where X can be 20, 24, 30, 36, 42 and 48 for output voltage, Y can be N (for with enclosure) or P (for without enclosure).

Model CEN-60-Y Series, where Y can be 12, 15, 20, 24, 30, 36, 42, 48 or 54 for output voltage and Model CEN-75-Y, where Y can be 15, 20, 24, 30, 36, 42, 48 or 54 for output voltage.

Marking: Company name, model designation and the Recognized Component Mark 

[Last Updated](#) on 2010-11-17

[Questions?](#)[Print this page](#)[Notice of Disclaimer](#)[Page Top](#)

[Copyright 2010 Underwriters Laboratories Inc.®](#)

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2010 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.





FKSZ8.E334687

Drivers for Light-emitting-diode Arrays, Modules and Controllers Certified for Canada - Component

[Page Bottom](#)

Drivers for Light-emitting-diode Arrays, Modules and Controllers Certified for Canada - Component

[See General Information for Drivers for Light-emitting-diode Arrays, Modules and Controllers Certified for Canada - Component](#)**MEAN WELL ENTERPRISES CO LTD**

E334687

28 WU-CHUAN 3RD RD
WUGU INDUSTRIAL PARK
TAIPEI HSIEN, 248 TAIWAN

LED drivers, Class 2 isolated output, Model CLY-100-Z, where Y can be G (for with Glue) or N (for without Glue), Z can be 12, 15, 20, 24, 27 and 36 for output voltage; Model PLN-100-Z, where Z can be 12, 15, 20, 24, 27 and 36 for output voltage; Models CLG-100-24DLU, CLG-100-24LU.

Model CLY-60-z, where y can be G (with potting compound) or N (without potting compound), z can be 12, 15, 20, 24, 27 and 36 for output voltage; Models PLN-60-z, PLN-45-z, where z can be 12, 15, 20, 24, 27 and 36 for output voltage, without potting compound.

Model HLG-100-YZ Series, where Y can be 20, 24, 30, 36, 42, 48 or 54 for output voltage, and Z can be blank, A or B.

Model HLG-100H-YZ Series, where Y can be 20, 24, 30, 36, 42, 48 or 54 for output voltage, and Z can be blank, A or B.

Isolated Class 2 LED power supplies, Models LPF-60X-YLU, where X may be blank or D, and Y may be 24 or 30 for output voltage.

LED drivers, other than Class 2, Model HLG-240H-yz, where y can be 12, 15, 20, 24, 30, 36, 42, 48, 54, z can be Blank, A, B or C; Model: HLG-240-yz, where y can be 12, 15, 20, 24, 30, 36, 42, 48 or 54, z can be Blank, A, B or C.

Model HLG-120-XZ Series, where X can be 12, 15, 20, 24, 30, 36, 42, 48 or 54 for output voltage, and Z can be blank, A or B.

Model HLG-120H-XZ Series, where X can be 12, 15, 20, 24, 30, 36, 42, 48 or 54 for output voltage, and Z can be blank, A or B.

Models HLG-150-XZ, HLG-185-YZ Series, where Y can be 12, 15, 20, 24, 30, 36, 42, 48 or 54 for output voltage, and Z can be blank, A or B.

Models HLG-150H-YZ, HLG-185-YZ Series, where Y can be 12, 15, 20, 24, 30, 36, 42, 48 or 54 for output voltage, and Z can be blank, A or B.

Isolated Class 2 LED power supplies, Model CEN-100-X, where X can be 20, 24, 30, 36, 42, 48 and 54 for output voltage.

Model PLY-20-X, where X can be 20, 24, 30, 36 and 42 for output voltage, Y can be N (for with enclosure) or P (for without enclosure).

Model CEN-60-Y Series, where Y can be 12, 15, 20, 24, 30, 36, 42, 48 or 54 for output voltage and Model CEN-75-Y, where Y can be 15, 20, 24, 30, 36, 42, 48 or 54 for output voltage.



Marking: Company name, model designation and the Recognized Component Mark

[Last Updated](#) on 2010-11-17

[Questions?](#)[Print this page](#)[Notice of Disclaimer](#)[Page Top](#)[Copyright ?2010 Underwriters Laboratories Inc.®](#)

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2010 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

